

INDUSTRIAL COMPONENT DATA

SAC-4PT-MS/2XFS VP NI 1065842 PHOENIX CONTACT T distributor, 4-position, unshielded, Plug straight M12, S-co..

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-4PT-MS/2XFS VP NI



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-4PT-MS/2XFS VP NI
Catalog number	1065842
Category	Sensor actuator adapter
Minimum order	1 Pcs
Document ID	EO-4E96C9DAF4
Generated	2026-08-05

Product Overview

T distributor, 4-position, unshielded, Plug straight M12, S-coded, on Socket straight M12, S-coded and Socket straight M12, S-coded, Parallel distributor

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Industrial Field Connectivity (IFC)

Additional Product Information

Key Commercial Data
 Orderkey 1065842
 Packing unit 1
 GTIN 4055626801988
 Custom tariff number 85444290
 Drawings
 General
 Standards and Regulations
 Ambient conditions
 Material
 Classifications
 Drawings
 Dimensional drawing
 M12 T-distributor

[Circuit diagram](#)

[Contact assignment of the M12 T distributor](#)

[Schematic diagram](#)

[Pin assignment of M12 connector, 3-pos.+PE, S-coded, pin side view](#)

[Schematic diagram](#)

[Pin assignment of M12 socket, 3-pos.+PE, S-coded, socket side view](#)

[Back to top](#)[Ambient conditions](#)

[Degree of protection IP65](#)

[IP67](#)

[Back to top](#)[General](#)

[Rated current at 40°C 12 A \(at 40 °C\)](#)

[Rated voltage 630 V AC](#)

[Number of positions 4](#)

[Color handle area black](#)

[Insulation resistance \$\geq 1 \text{ G}\Omega\$](#)

[Coding S power](#)

[Standards/regulations M12 connector IEC 61076-2-111](#)

[Status display No](#)

[Overvoltage category III](#)

[Degree of pollution 2](#)

[Insertion/withdrawal cycles \$> 100\$](#)

[Back to top](#)[Material](#)

[Contact material CuZn](#)

[Contact surface material Au](#)

[Contact carrier material PA](#)

[Material of grip body TPU](#)

[Material, knurls Zinc die-cast, nickel-plated](#)

[Sealing material FKM](#)

[Back to top](#)[Standards and Regulations](#)

[Standards/specifications M12 connector IEC 61076-2-111](#)

[Back to top](#)[Classifications](#)

[eCl@ss](#)

[eCl@ss 9.0 27440106](#)

[Back to top](#)[ETIM](#)

[ETIM 6.0 EC002925](#)

[ETIM 7.0 EC002925](#)

[Back to top](#)

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-4PT-MS/2XFS VP NI with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.