

INDUSTRIAL COMPONENT DATA

SAC-5P- 0,5-290/M12FSL FE 1348664 PHOENIX CONTACT

Power cable, 5-pole, halogen-free PUR, grey RAL 7001, free..

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-5P-0,5-290/M12FSL FE



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-5P-0,5-290/M12FSL FE
Catalog number	1348664
Category	Sensor-actuator patch cord
Minimum order	25 Pcs
Document ID	EO-09AD3C1C2C
Generated	2026-08-05

Product Overview

Power cable, 5-pole, halogen-free PUR, grey RAL 7001, free cable end, to straight female M12, coding: L, cable length: 0.5 m, for direct current up to 12 A/63 V

Power cable, 5-pole, halogen-free PUR, grey RAL 7001, Straight connect female M12, coding: L, free cable end, cable length: 0.5 m, for direct current up to 12 A/63 V

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Industrial Field Connectivity (IFC)

Additional Product Information

ETIM for 1348664 Sensors (EC001855)

Feature Name

Feature Value

Number of poles (EF001391)

5

Type of electrical connection, field-sided (EF005525)

Other

Positioning cable feed, field-sided (EF005928)

Other

Type of electrical connection, box-sided (EF005524)

M12

Type of plug-in contact, box-sided (EF008386)

Female (bus)
Positioning cable feed, box-sided (EF005927)
Straight
Cable length (EF000536)
0.5 m
Material of cable sheath (EF004136)
Other
Halogen free (EF000025)
Yes
Colour cable sheath (EF008249)
Other
With LED indication (EF005950)
No
Screened (EF000881)
No
Vulcanize (EF004115)
No
Material contact body (EF008248)
Other
Material of contact surface (EF004020)
Other
Permitted cable outer temperature after assembling without vibration (EF001686)
-50 °C
Permitted cable outer temperature during assembling/handling (EF001685)
-30 °C
Rated voltage (EF000228)
63 V
Degree of protection (IP) (EF005474)
IP65

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-5P-0,5-290/M12FSL FE with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.