

INDUSTRIAL COMPONENT DATA

SAC-5P- 0,5-920/M12FS 1519370 PHOENIX CONTACT Bus system cable

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-5P-0,5-920/M12FS



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-5P-0,5-920/M12FS
Catalog number	1519370
Category	Sensor-actuator patch cord
Minimum order	1 Pcs
Document ID	EO-53E992456D
Generated	2026-08-02

Product Overview

Bus system cable

Bus System Cable, CANopen®, DeviceNet™, 5-pole halogen-free, shielded, free cable end, to Elbowed Female M12, encoding: A, cable length: 0.5 m

Bus system cable, CANopen®, DeviceNet™, 5-position, PUR halogen-free, red lilac RAL 4001, shielded, free cable end, on Socket straight M12, coding: A, cable length: 0.5 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Field Connectivity (IFC)
--------------	---

Additional Product Information

Technical dataProduct propertiesProduct type Data cable preassembled

Sensor type CANopen®

Number of positions 5

Shielded yes

Insulation characteristics

Overvoltage category II

Degree of pollution 3

InterfacesBus system CANopen®/DeviceNet™

Signal type/category CANopen®

DeviceNet™

SignalingStatus display no

Status display present No

Electrical propertiesInsulation resistance $\geq 100 \text{ M}\Omega$

Nominal voltage UN 48 V AC
60 V DC

Nominal current IN 4 A

Mechanical propertiesMechanical data

Insertion/withdrawal cycles ≥ 100

Material specificationsFlammability rating according to UL 94 HB

Seal material NBR

Material of grip body TPU, hardly inflammable, self-extinguishing

Contact material CuSn

Contact surface material Ni/Au

Contact carrier material TPU GF

Material for screw connection Zinc die-cast, nickel-plated

ConnectorConnection 1

Type free cable end

Connection 2

Type free cable end

Cable/lineCable length 0.5 m

CANopen®/DeviceNet™, PUR, violet [920]

Dimensional drawing

Cable weight 90 kg/km

UL AWM Style 21198 (80°C/300 V)

Number of positions 4

Shielded yes

Cable type CANopen®/DeviceNet™, PUR, violet [920]

Conductor structure 2xAWG24/19+2xAWG22/19

Conductor structure signal line 19x 0.13 mm

AWG signal line 24

Conductor cross section 2x 0.25 mm² (Data cable)
2x 0.34 mm² (Power supply)
1x 0.34 mm² (Drain wire)

Wire diameter incl. insulation 1.95 mm $\pm 0.05 \text{ mm}$ (Data cable)
1.4 mm $\pm 0.05 \text{ mm}$ (Power supply)

External cable diameter 6.70 mm $\pm 0.3 \text{ mm}$

Outer sheath, material PUR

External sheath, color re...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-5P-0,5-920/M12FS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.