

**INDUSTRIAL COMPONENT DATA**

# HCS-T MINI 1W 3AA C C 7035 2203134 PHOENIX CONTACT

## Electronic housing

Brand: PHOENIX CONTACT | Manufacturer Part Number: HCS-T MINI 1W 3AA C C 7035



|                 |                            |
|-----------------|----------------------------|
| Manufacturer    | PHOENIX CONTACT            |
| MPN / Reference | HCS-T MINI 1W 3AA C C 7035 |
| Catalog number  | 2203134                    |
| Category        | Electronic enclosure       |
| Minimum order   | 1 Pcs                      |
| Document ID     | EO-6A45A135BC              |
| Generated       | 2026-08-06                 |

### Product Overview

Electronic housing

T-Mini portable housing in light grey, consisting of two halves with screws. Front with 1.1 mm reinforcement, with window and keyboard slot, battery compartment cover and battery contacts for 3 AA batteries

**STRUCTURED PRODUCT DATA**

### Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

### Classification & Catalog Path

Catalog path **PHOENIX CONTACT > Housing (HS)**

### Additional Product Information

Key Commercial Data

Orderkey 2203134

Packing unit 1 pc

GTIN 4055626376882

Weight per Piece (excluding packing) 180.200 g

Custom tariff number 39269097

Country of origin DE (Germany)

Item properties

Type HCS-T MINI 1W 3AA C C 7035

Order No. 2203134

Housing type Handheld housing

Type stepped

Battery compartment 3 x AA

**Measurements****Dimensional drawing**

Caption Schematic representation - for additional information, see product range drawing in the Download Center

Width [ w ] 85 mm

Height [ h ] 182.5 mm

Depth [ d ] 30 mm

Diagonal 2.8 in. (Window for display)

Dimensions x 1.1 mm (Recessed area on front)

62 mm x 32.6 mm (Window for display)

41 mm x 3.5 mm (Opening for membrane cable)

**Material specifications**

Color (RAL) light gray (7035)

Flammability rating according to UL 94 V0

Housing material ABS

Hammer test

Specification IEC 60068-2-75:2014-09

Impact energy 0.7 J

Number of drop cycles 5

Thermostability (ball thrust test)

Specification IEC 60695-10-2:2014-02

Temperature 80 °C

Test duration 1 h

Force 20

Test for assessing the risk of fire (glow wire)

Specification IEC 60695-2-11:2014-02

Temperature 850 °C

Time of exposure 30 s

Degrees of protection provided by enclosures (IP code)

Specification IEC 60529:1989-11 + AMD 1:1999-11 + AMD 2:2013-08

Result, degree of protection, IP code IP40

**Packaging information**

Pieces per package 1

Denomination packing units Pcs.

**Standards and regulations**

Flammability rating according to UL 94 V0

**Classifications**

eCI@ss 5.127180506eCI@ss 6.027180800eCI@...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / HCS-T MINI 1W 3AA C C 7035 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.