

INDUSTRIAL COMPONENT DATA

SAC-5P-0,75-115/M 8SIFSB 1525563 PHOENIX CONTACT

Sensor/Actuator Cable, 5-Pole, Free Cable End, A Straight F..

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-5P-0,75-115/M 8SIFSB



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-5P-0,75-115/M 8SIFSB
Catalog number	1525563
Category	Sensor-actuator patch cord
Minimum order	100 Pcs
Document ID	EO-E48E296704
Generated	2026-08-05

Product Overview

Sensor/Actuator Cable, 5-Pole, Free Cable End, A Straight Female M8 Snap-in, Coding: B, Cable Length: 0.75 m

Cable for sensors/actuators

Sensor/actuator cable, 5-position halogen-free, free cable end, on Socket straight M8 Snap-in, coding: A, cable length: 0.75 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Industrial Field Connectivity (IFC)

Additional Product Information

Technical dataProduct propertiesProduct type Sensor/actuator cable

Number of positions 5

No. of cable outlets 1

Shielded no

Insulation characteristics

Overvoltage category II

Degree of pollution 3

Material specificationsFlammability rating according to UL 94 HB

Seal material NBR

Material of grip body TPU, hardly inflammable, self-extinguishing

Contact material CuSn

Contact surface material Ni/Au

Contact carrier material TPU GF
Material for screw connection Zinc die-cast, nickel-plated
Electrical properties Contact resistance $\leq 5 \text{ m}\Omega$
Insulation resistance $\geq 100 \text{ M}\Omega$
Nominal voltage UN 30 V AC
30 V DC
Nominal current IN 4 A
Signaling Status display No
Status display present No
Connector Connection 1
Type free cable end
Connection 2
Type Socket straight M8 Snap-in
Locking type Snap-in
Coding type A (Standard)
Cable/line Cable length 0.75 m
PUR, black, 5th conductor gray [115]
Shielded no
UL AWM Style 20549
Cable weight 30 kg/km
Cable type PUR, black, 5th conductor gray
Short symbol Li9Y11Y
Cable type (abbreviation) 115
External cable diameter 4.7 mm $\pm 0.15 \text{ mm}$
Outer sheath, material PUR
External sheath, color black-gray RAL 7021
Conductor material Bare Cu litz wires
Conductor structure signal line 32x 0.10 mm
AWG signal line 24
Conductor cross section 0.25 mm²
Material, filler PP
Material wire insulation PP
Thickness, insulation approx. 0.21 mm (Core insulation)
Wire diameter incl. insulation 1.17 mm $\pm 0.02 \text{ mm}$
Single wire, color brown, white, blue, black, gray
Overall twist 5 cores, twis...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-5P-0,75-115/M 8SIFSB with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.