

INDUSTRIAL COMPONENT DATA

SAC-5P-10,0-515/M12FS VA E-UL 1031272 PHOENIX CONTACT Cable for sensors/actuators 5-pin, PVC, black RAL 9005..

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-5P-10,0-515/M12FS VA E-UL



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-5P-10,0-515/M12FS VA E-UL
Catalog number	1031272
Category	Sensor-actuator patch cord
Minimum order	50 Pcs
Document ID	EO-B4DD8214D8
Generated	2026-08-06

Product Overview

Cable for sensors/actuators 5-pin, PVC, black RAL 9005, cable length: 10 m, Knurled stainless steel
 Sensor/Actuator Cable, 5-Pole, PVC, Black RAL 9005, Free Cable End, to Straight Connecting Female M12, Coding: A,
 Cable Length: 10 m
 Sensor/actuator cable, 5-pole, PVC, black RAL 9005, free cable end, to Straight female M12, coding: A, cable length: 10 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Field Connectivity (IFC)
--------------	---

Additional Product Information

Cable for sensors/actuators 5-pin, PVC, black RAL 9005, end of free cable, Female straight connection M12, coded, cable length: 10 m
 Data commercial
 Key order One million thirty one thousand two hundred seventy two
 Packing unit 1 pcs
 Key selling BF1CDA -
 Minimum order quantity 50 pcs
 EAN Four trillion fifty five billion six hundred twenty six million five hundred thirty four thousand seven hundred seventy
 Unit weight (excluding packaging) 531,000 g
 Tariff number tariff Eighty five million four hundred forty four thousand two hundred ninety

Measures

Cable length 10 m

Environmental conditions

Room temperature (service) -25 °C ... 90 °C (male / female)

Index of protection IP65

IP67

IP68

IP69K

Overview

Current sizing at 40 °C 4 To

Tension sizing 48 V AC

60 V DC

Number of poles Five

Insulation resistance $\geq 100 \text{ M}\Omega$

Encoding A - standard

Standards/specifications Plug-in connector M12 to IEC 61076-2-101

Status indication Not

Protective circuit/component protection without connect

Category surge II

Pollution degree Three

Cycles of plug ≥ 100 **Material**

Class of flammability according to UL 94 HB

Material contact CuSn

Material contact surface Ni/Au

Material support of contacts TPU GF

Material body grip TPU fire-retardant, self-extinguishing

Material knurled Stainless steel 1.4404

Standards and specifications

Name of standard Plug-in connector M12

Standards/specifications IEC 61076-2-101

Class of flammability according to UL 94 HB

Cable

Type of cable Black PVC 5. Driver gray

Cable type (a...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-5P-10,0-515/M12FS VA E-UL with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.