

INDUSTRIAL COMPONENT DATA

SAC-5P-100,0-920 1420416 PHOENIX CONTACT Cable

SAC-5P-100,0-920 1420416

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-5P-100,0-920



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-5P-100,0-920
Catalog number	1420416
Category	Flexible cable
Minimum order	1 Pcs
Document ID	EO-10B1E371CC
Generated	2026-08-05

Product Overview

Cable - SAC-5P-100,0-920 - 1420416

By the Meter, Cable Ring, CANopen®, DeviceNet™, shielded, halogen-free PUR, violet RAL 4001, 4-conductors (2xAWG24/19+2xAWG22/19), single conductor colour: red-black, blue-white, cable length: 100 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > Industrial Field Connectivity (IFC)**

Additional Product Information

Cable ring, DeviceNet™/CANopen®, 4-wire, shielded, halogen-free PUR, violet outer sheath, 2 x 0.34 mm², 2 x 0.25 mm², cable length: 100 m

Key Commercial Data

Orderkey 1420416

Packing unit 1

GTIN 4055626213996

Custom tariff number 85444995

Dimensions

Length of cable 100 m

General

Number of positions 4

Signal type/category CANopen®

DeviceNet™

Cable

Cable type CAN Bus/DeviceNet

Cable type (abbreviation) 920

UL AWM style 21198 (80°C/300 V)

Cable structure 2xAWG24/19+2xAWG22/19

Conductor cross section 2x 0.25 mm² (Data cable)2x 0.34 mm² (Power supply)1x 0.34 mm² (Drain wire)

AWG signal line 24

AWG power supply 22

Conductor structure signal line 19x 0.13 mm

Conductor structure, voltage supply 19x 0.15 mm

Core diameter including insulation 1.95 mm ±0.05 mm (Data cable)

1.4 mm ±0.05 mm (Power supply)

Wire colors Red-black, blue-white

Twisted pairs 2 cores to the pair

Type of pair shielding Plastic-coated aluminum foil, aluminum side outside

Overall twist 2 pairs around a drain wire in the center to the core

Shielding Tinned copper braided shield

Optical shield covering 80 %

External sheath, color violet RAL 4001

External cable diameter D 6.7 mm ±0,3 mm

Minimum bending radius, fixed installation 5 x D

Minimum bending radius, flexible installation 10 x D

Number of bending cycles 5000000

Bending radius 70 mm

Minimum bending radius, drag chain applications 10 x D

Traversing path 4.5 m

Traversing rate 3 m/s

Acceleration 3 m/s²

Cable weight 90 kg/km

Outer sheath, material PUR

Material c...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-5P-100,0-920 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.