


INDUSTRIAL COMPONENT DATA

SAC-5P-15,0-PUR/M12FR 1402146 PHOENIX CONTACT

Sensor/actuator cable

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-5P-15,0-PUR/M12FR



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-5P-15,0-PUR/M12FR
Catalog number	1402146
Category	Sensor-actuator patch cord
Minimum order	1 Pcs
Document ID	EO-64D6C67421
Generated	2026-08-04

Product Overview

Sensor/actuator cable

Sensor/Actuator Cable, 5-pole halogen-free, free cable end, to Elbow Female M12, coding: A, cable length: 15 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Field Connectivity (IFC)
--------------	---

Additional Product Information

Key Commercial Data

Orderkey 1402146

Packing unit 1

GTIN 4046356585989

Custom tariff number 85444290

Dimensions

Length of cable 15 m

Stripping length of the free conductor end 50 mm

Ambient conditions

Ambient temperature (operation) -25 °C ... 90 °C (Plug / socket)

Degree of protection IP65

IP67

IP68

General

Rated current at 40°C 4 A
Rated voltage 48 V AC
60 V DC
Number of positions 5
Insulation resistance $\geq 100 \text{ M}\Omega$
Coding A - standard
Status display No
Overvoltage category II
Degree of pollution 3
Insertion/withdrawal cycles ≥ 100
Material
Flammability rating according to UL 94 HB
Contact material CuSn
Contact surface material Ni/Au
Contact carrier material TPU GF
Material of grip body TPU, hardly inflammable, self-extinguishing
Material, knurls Zinc die-cast, nickel-plated
Sealing material NBR
Standards and Regulations
Flammability rating according to UL 94 HB
Cable
Cable type PUR halogen-free black
Cable type (abbreviation) PUR
UL AWM style 20549
Conductor cross section $5 \times 0.34 \text{ mm}^2$ (Signal line)
AWG signal line 22
Conductor structure signal line $42 \times 0.10 \text{ mm}$
Core diameter including insulation $1.27 \text{ mm} \pm 0.02 \text{ mm}$ (Signal line)
Thickness, insulation approx. 0.5 mm
Wire colors brown, white, blue, black, green-yellow
External sheath, color black-gray RAL 7021
External cable diameter $D 4.55 \text{ mm} \pm 0.15 \text{ mm}$
Smallest bending radius, fixed installation 23 mm
Smallest bending radius, movable installation 46 mm
Number of bending cycles 10000000
Bending radius 50 mm
Traversing path 10 m
Trav...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-5P-15,0-PUR/M12FR with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.