

INDUSTRIAL COMPONENT DATA

SAC-5P-20,0-547/M12FS BK 1425125 PHOENIX CONTACT

Sensor/actuator cable

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-5P-20,0-547/M12FS BK



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-5P-20,0-547/M12FS BK
Catalog number	1425125
Category	Sensor-actuator patch cord
Minimum order	1 Pcs
Document ID	EO-E09E661F1B
Generated	2026-08-03

Product Overview

Sensor/actuator cable

Sensor/Actuator Cable, 5-Pole, PVC, Yellow, Free Cable End, to Straight Connecting Female M12, Encoding: A, Cable Length: 20 m

Sensor/actuator cable, 5-position, PVC, yellow, free cable end, on Socket straight M12, coding: A, cable length: 20 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Field Connectivity (IFC)
--------------	---

Additional Product Information

Technical dataProduct propertiesProduct type Sensor/actuator cable

Application Standard, U.S. cables

Number of positions 5

No. of cable outlets 1

Shielded no

Coding A

Insulation characteristics

Overvoltage category II

Degree of pollution 3

Material specificationsFlammability rating according to UL 94 HB

Seal material NBR

Material of grip body TPU, hardly inflammable, self-extinguishing

Contact material CuSn
Contact surface material Ni/Au
Contact carrier material TPU GF
Material for screw connection Zinc die-cast, nickel-plated
Outer sheath, material PVC
Electrical properties Insulation resistance $\geq 10\text{ M}\Omega$
Nominal voltage UN 48 V AC
60 V DC
Nominal current I_N 4 A
Signaling Status display no
Status display present No
Connection data Conductor connection
Tightening torque 0.4 Nm (M12 connector)
Connector Connection 1
Type free cable end
Connection 2
Type Socket straight M12
Number of positions 5
Coding type A
Cable/line Cable length 20 m
PVC AWG 18 yellow 105°C [547]
Dimensional drawing
UL AWM Style 2517 (105 °C / 300 V)
Number of positions 5
Shielded no
Cable type PVC AWG 18 yellow 105°C [547]
Conductor structure signal line 41x 0.16 mm
AWG signal line 18
Wire diameter incl. insulation 1.7 mm $\pm 0.03\text{ mm}$
External cable diameter 6.60 mm $\pm 0.2\text{ mm}$
Outer sheath, material PVC
External sheath, color yellow
Conductor material Tin-plated Cu litz wires
Material, filler PP
Material wire insulation PVC
Single wire, color brown, white, blue, black, gray
Overall twist 5 wires around filler to the co...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-5P-20,0-547/M12FS BK with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.