

INDUSTRIAL COMPONENT DATA

SAC-5P-20,0-600/M12FR HD 1420761 PHOENIX CONTACT

Sensor/actuator cable SAC-5P-20,0-600/M12FR HD 1420761

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-5P-20,0-600/M12FR HD



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-5P-20,0-600/M12FR HD
Catalog number	1420761
Category	Sensor-actuator patch cord
Minimum order	25 Pcs
Document ID	EO-AD0C59831D
Generated	2026-08-06

Product Overview

Sensor/actuator cable - SAC-5P-20,0-600/M12FR HD - 1420761

Sensor/actuator cable, 5-pole, halogen-free PP-EPDM, grey RAL 7035, free cable end, to Elbowed Female M12, coding: A, cable length: 20 m, Hygienic design, with stainless steel knurling

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Field Connectivity (IFC)
--------------	---

Additional Product Information

Sensor/actuator cable, 5-position, PP-EPDM halogen-free, gray RAL 7035, cable length: 20 m, Hygienic design, with high-grade steel knurl

Key Commercial Data

Orderkey 1420761

Packing unit 1

GTIN 4055626238814

Custom tariff number 85444290

Dimensions

Length of cable 20 m

Ambient conditions

Ambient temperature (operation) -40 °C ... 105 °C (Plug / socket)

General

Rated current at 40°C 4 A

Rated voltage 48 V AC
60 V DC
Number of positions 5
Coding A - standard
Standards/regulations M12 connector IEC 61076-2-101
Material conformance FDA 21 CFR 177.2600
Status display No
Protective circuit/component unwired
Overvoltage category II
Degree of pollution 3
Material
Contact material CuSn
Contact surface material Ni/Au
Contact carrier material PP
Material of grip body PP
Material, knurls Stainless steel
Sealing material FKM
Standards and Regulations
Standard designation M12 connector
Standards/regulations IEC 61076-2-101
Standard designation Material conformance
Standards/regulations FDA 21 CFR 177.2600
Cable
Cable type Halogen-free PP gray
Cable type (abbreviation) 600
Cable abbreviation Li9Y9Y
Conductor cross section 5x 0.34 mm² (Signal line)
AWG signal line 22
Conductor structure signal line 42x 0.10 mm
Core diameter including insulation 1.27 mm ±0.02 mm (Signal line)
Thickness, insulation ≥ 0.21 mm (Core insulation)
Wire colors Brown, white, blue, black, gray
Overall twist 5 cores, twisted
Length of twist, overall twist 55 mm
External sheath, color gray RAL 7035
Outer sheath thickne...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-5P-20,0-600/M12FR HD with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.