

INDUSTRIAL COMPONENT DATA

SAC-5P-25,0-28X/M12FS SH OD 1533789 PHOENIX CONTACT Sensor/Actuator Cable, 5-Pole, Free Cable End, to Straig..

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-5P-25,0-28X/M12FS SH OD



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-5P-25,0-28X/M12FS SH OD
Catalog number	1533789
Category	Sensor-actuator patch cord
Minimum order	20 Pcs
Document ID	EO-5733897830
Generated	2026-08-05

Product Overview

Sensor/Actuator Cable, 5-Pole, Free Cable End, to Straight Female M12, Coding: A, Cable Length: 25 m, Outdoor Application, Stainless Steel Knurling

Cable for sensors/actuators

Sensor/actuator cable, 5-position, free cable end, on Socket straight M12, coding: A, cable length: 25 m, for outdoor applications, with high-grade steel knurl

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Industrial Field Connectivity (IFC)

Additional Product Information

Technical dataProduct propertiesProduct type Sensor/actuator cable

Number of positions 5

Application External areas

No. of cable outlets 1

Shielded yes

Coding A

Insulation characteristics

Degree of pollution 3

Material specificationsFlammability rating according to UL 94 V0

Seal material FPM

Material of grip body PP

Contact material CuSn
Contact surface material Ni/Au
Contact carrier material PP
Material for screw connection Stainless steel
Electrical propertiesContact resistance $\leq 5 \text{ m}\Omega$?
Insulation resistance $\geq 100 \text{ M}\Omega$?
Nominal voltage UN 48 V AC
60 V DC
Nominal current IN 4 A
Protective circuit unwired
Mechanical propertiesMechanical data
Insertion/withdrawal cycles ≥ 100
SignalingStatus display No
Status display present No
ConnectorConnection 1
Type free cable end
Connection 2
Type Socket straight M12
Number of positions 5
Coding type A
Cable/lineCable length 25 m
PE-X black [28X]
Dimensional drawing
Shielded yes
Cable weight 85 kg/km
Cable type PE-X black
Short symbol Li2X2X-C-V1-2X
Cable type (abbreviation) 28X
External cable diameter 7.25 mm $\pm 0.3 \text{ mm}$
Outer sheath, material PE-X
External sheath, color black-gray RAL 7021
Thickness, outer sheath approx. 0.7 mm
Material, inner sheath PE-X
Inner sheath thickness approx. 0.5 mm
Conductor material Bare Cu litz wires
Conductor structure signal line 28x 0.15 mm
AWG signal line 20
Conductor cross section 5x 0.5 mm²
Material, filler PP yarn
Material wire insulation PE-X
Thickness, insulation approx. 0.3 mm (Core insulation)
Wire diam...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-5P-25,0-28X/M12FS SH OD with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.