

INDUSTRIAL COMPONENT DATA

SAC-5P-3,0-280/M12FSL FE CH-MA 1158836 PHOENIX CONTACT Power cable, 5-pole, halogen-free PUR, grey RAL 7001,..

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-5P-3,0-280/M12FSL FE CH-MA



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-5P-3,0-280/M12FSL FE CH-MA
Catalog number	1158836
Category	Sensor-actuator patch cord
Minimum order	100 Pcs
Document ID	EO-0B4729F72E
Generated	2026-08-05

Product Overview

Power cable, 5-pole, halogen-free PUR, grey RAL 7001, free cable end, to straight female M12, coding: L, cable length: 3 m, for direct current up to 16 A / 63 V, Customer variant

Power cable, 5-pole, halogen-free PUR, grey RAL 7001, Straight connection female M12, coding: L, free cable end, cable length: 3 m, for direct current up to 16 A / 63 V, Customer variant

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Industrial Field Connectivity (IFC)

Additional Product Information

ETIM for 1158836 Sensors (EC001855)

Feature Name

Feature Value

Number of poles (EF001391)

5

Type of electrical connection, field-sided (EF005525)

Other

Positioning cable feed, field-sided (EF005928)

Other

Type of electrical connection, box-sided (EF005524)

M12

Type of plug-in contact, box-sided (EF008386)

Female (bus)

Positioning cable feed, box-sided (EF005927)

Straight

Cable length (EF000536)

3 m

Material of cable sheath (EF004136)

Other

Halogen free (EF000025)

Yes

Colour cable sheath (EF008249)

Other

With LED indication (EF005950)

No

Screened (EF000881)

No

Vulcanize (EF004115)

No

Material contact body (EF008248)

Other

Material of contact surface (EF004020)

Other

Permitted cable outer temperature after assembling without vibration (EF001686)

-50 °C

Permitted cable outer temperature during assembling/handling (EF001685)

-30 °C

Rated voltage (EF000228)

63 V

Degree of protection (IP) (EF005474)

IP65

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-5P-3,0-280/M12FSL FE CH-MA with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten PI #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.