

INDUSTRIAL COMPONENT DATA

SAC-5P- 3,0-PUR/M12FRK PE 1414784 PHOENIX CONTACT

Power cable, 5-position, PUR halogen-free, black-gray RAL ..

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-5P-3,0-PUR/M12FRK PE



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-5P-3,0-PUR/M12FRK PE
Catalog number	1414784
Category	Sensor-actuator patch cord
Minimum order	1 Pcs
Document ID	EO-6A942BE4F3
Generated	2026-08-05

Product Overview

Power cable, 5-position, PUR halogen-free, black-gray RAL 7021, Socket angled M12, K-coded, on free cable end, cable length: 3 m, for AC current up to 16 A/690 V

Power cable, 5-pole halogen-free, free cable end, to Angled Female M12, coding: K, cable length: 3 m, for alternating current up to 16 A/690 V

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Field Connectivity (IFC)
--------------	---

Additional Product Information

Key Commercial Data

Orderkey 1414784

Packing unit 1 pc

Catalog page Page 292 (C-2-2019)

GTIN 4055626034188

Weight per Piece (excluding packing) 1,760.000 g

Custom tariff number 85444290

Country of origin PL (Poland)

Drawings

Ambient conditions

Material

Cable

[Classifications](#)

[Dimensions](#)

[General](#)

[Standards and Regulations](#)

[Environmental Product Compliance](#)

[Drawings](#)

[Diagram](#)

[Dimensional drawing](#)

[M12 x 1 socket, angled](#)

[Circuit diagram](#)

[Contact assignment of the M12 socket](#)

[Schematic diagram](#)

[Pin assignment of M12 socket, 5-pos., K-coded, socket side view](#)

[Cable cross section](#)

[PUR halogen-free black \[PUR\]](#)

[Back to top](#)[Dimensions](#)

[Length of cable 3 m](#)

[Back to top](#)[Ambient conditions](#)

[Ambient temperature \(operation\) -25 °C ... 85 °C \(Plug / socket\)](#)

[Degree of protection IP65](#)

[IP67](#)

[Back to top](#)[General](#)

[Rated current at 40°C 16 A](#)

[Rated voltage 690 V AC](#)

[Number of positions 5](#)

[Color handle area black](#)

[Insulation resistance >= 100 M?](#)

[Coding K - Power](#)

[Standards/regulations M12 connector IEC 61076-2-111](#)

[Status display No](#)

[Protective circuit/component unwired](#)

[Overvoltage category III](#)

[Degree of pollution 3](#)

[Insertion/withdrawal cycles >= 100](#)

[Torque 0.4 Nm \(M12 connector\)](#)

[Back to top](#)[Material](#)

[Flammability rating according to UL 94 V0](#)

[Contact material CuZn](#)

[Contact surface material Ni/Au](#)

[Contact carrier material PA](#)

[Material of grip body PP](#)

[Material, knurls Zinc die-cast, nickel-plated](#)

[Back to top](#)[Standards and Regulations](#)

[Standards/specifications M12 connector IEC 61076-2-111](#)

[Flammability rating according to UL 94 V0](#)

[Back...](#)

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-5P-3,0-PUR/M12FRK PE with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.