


INDUSTRIAL COMPONENT DATA

SAC-5P- 3,0-PUR/M12FSK PE SH 1414789 PHOENIX CONTACT Power cable

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-5P-3,0-PUR/M12FSK PE SH



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-5P-3,0-PUR/M12FSK PE SH
Catalog number	1414789
Category	Sensor-actuator patch cord
Minimum order	1 Pcs
Document ID	EO-50A0254538
Generated	2026-08-05

Product Overview

Power cable

Power cable, 5-pole halogen-free, shielded (Advanced Shielding Technology), free cable end, to straight female M12, encoding: K, cable length: 3 m, for AC current up to 16 A/690 V

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Industrial Field Connectivity (IFC)

Additional Product Information

Key Commercial Data

Orderkey 1414789

Packing unit 1 pc

Note Made to Order (non-returnable)

Catalog page Page 296 (C-2-2017)

GTIN 4055626034232

Weight per Piece (excluding packing) 638.030 g

Custom tariff number 85444290

Country of origin PL (Poland)

Dimensions

Length of cable 3 m

Ambient conditions

Ambient temperature (operation) -25 °C ... 85 °C (Plug / socket)

Degree of protection IP65

IP67

IP68

General

Rated current at 40°C 16 A

Rated voltage 690 V AC

Number of positions 5

Color handle area black

Insulation resistance $\geq 100 \text{ M}\Omega$

Coding K - Power

Standards/regulations M12 connector IEC 61076-2-111

Status display No

Protective circuit/component unwired

Overvoltage category III

Degree of pollution 3

Insertion/withdrawal cycles ≥ 100

Torque 0.4 Nm (M12 connector)

Material

Flammability rating according to UL 94 V0

Contact material CuSn

Contact surface material Ni/Au

Contact carrier material PA

Material of grip body PA

Material, knurls Zinc die-cast, nickel-plated

Standards and Regulations

Standard designation M12 connector

Standards/regulations IEC 61076-2-111

Flammability rating according to UL 94 V0

Cable

Cable type PUR halogen-free orange

Cable type (abbreviation) PUR

UL AWM style 22078 / 11560 (90 °C / 1000 V)

Conductor cross section 5x 2.5 mm²

AWG power supply 14

Conductor structure, voltage supply 141x 0.15 mm

Core diameter including insulation 2.8 mm $\pm 0.1 \text{ mm}$

Thickness, insulation $\geq 0.36 \text{ mm}$

Wire colors Black 1, black 2, black 3, black 4, green/yellow

External sheath, color...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-5P-3,0-PUR/M12FSK PE SH with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.