

INDUSTRIAL COMPONENT DATA

SAC-5P-40,0-921/M12FS 1582047 PHOENIX CONTACT Bus System Cable, CANopen, DeviceNet, 5-pole, free cable end, ..

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-5P-40,0-921/M12FS



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-5P-40,0-921/M12FS
Catalog number	1582047
Category	Sensor-actuator patch cord
Minimum order	25 Pcs
Document ID	EO-325D06B9D2
Generated	2026-08-05

Product Overview

Bus System Cable, CANopen, DeviceNet, 5-pole, free cable end, to Straight female M12, encoding: A, cable length: 40 m
Cable for sensors/actuators

Bus system cable, CANopen®, DeviceNet™, 5-position, free cable end, on Socket straight M12, coding: A, cable length: 40 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Field Connectivity (IFC)
--------------	---

Additional Product Information

Technical dataProduct propertiesProduct type Data cable preassembled

Sensor type CANopen®

Number of positions 5

Application Bus system

No. of cable outlets 1

Coding A

Insulation characteristics

Overvoltage category II

Degree of pollution 3

InterfacesBus system CANopen®/DeviceNet™

Signal type/category CANopen®

DeviceNet™

SignalingStatus display No
Status display present No
Electrical propertiesContact resistance $\leq 5 \text{ m}\Omega$?
Insulation resistance $\geq 100 \text{ M}\Omega$?
Nominal voltage UN 48 V AC
60 V DC
Nominal current IN 4 A
Transmission medium Copper
Mechanical propertiesMechanical data
Insertion/withdrawal cycles ≥ 100
Material specificationsFlammability rating according to UL 94 HB
Seal material NBR
Material of grip body TPU, hardly inflammable, self-extinguishing
Contact material CuSn
Contact surface material Ni/Au
Contact carrier material TPU GF
Material for screw connection Zinc die-cast, nickel-plated
ConnectorConnection 1
Type free cable end
Connection 2
Type Socket straight M12
Number of positions 5
Coding type A (Standard)
Cable/lineCable length 40 m
CANopen®/DeviceNet™, PUR, black [921]
Dimensional drawing
Shielded yes
UL AWM Style 21198 (80°C/300 V)
Cable weight 90 kg/km
Cable type CANopen®/DeviceNet™, PUR, black
Cable type (abbreviation) 921
Signal type/category CANopen®
DeviceNet™
Cable structure 2xAWG24/19+2xAWG22/19
External cable diameter 6.7 mm $\pm 0.3 \text{ mm}$
Outer sheath, material PUR
External sheath, color black RAL 9005
Conductor material Tin-plated Cu litz wires
Conductor structu...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-5P-40,0-921/M12FS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.