

**INDUSTRIAL COMPONENT DATA**

# SAC-5P- 5,0-BF145/M12FS SH 1403272 PHOENIX CONTACT

## Sensor/actuator cable SAC-5P- 5,0-BF145/M12FS SH 1403272

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-5P- 5,0-BF145/M12FS SH



|                 |                            |
|-----------------|----------------------------|
| Manufacturer    | PHOENIX CONTACT            |
| MPN / Reference | SAC-5P- 5,0-BF145/M12FS SH |
| Catalog number  | 1403272                    |
| Category        | Sensor-actuator patch cord |
| Minimum order   | 25 Pcs                     |
| Document ID     | EO-1E2A9AB3EF              |
| Generated       | 2026-08-05                 |

### Product Overview

Sensor/actuator cable - SAC-5P- 5,0-BF145/M12FS SH - 1403272

**STRUCTURED PRODUCT DATA**

### Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

### Classification & Catalog Path

Catalog path      PHOENIX CONTACT &gt; Industrial Field Connectivity (IFC)

### Additional Product Information

Sensor/actuator cable, POC halogen-free, irradiated, black RAL 9005, shielded

Key Commercial Data

Orderkey 1403272

Packing unit 1

GTIN 4046356646444

Custom tariff number 85444290

General

Rated voltage 48 V AC

60 V DC

Cable

Cable type POC irradiated halogen-free black

Cable type (abbreviation) BF 145

Conductor cross section 5x 0.5 mm²

AWG signal line 20

Core diameter including insulation 1.9 mm

Wire colors black 1, black 2, black 3, black 4, black 5  
Overall twist 5 wires around filler to the core  
Shielding Tinned copper braided shield  
External sheath, color black RAL 9005  
External cable diameter D 7.3 mm  
Minimum bending radius, fixed installation 4 x D  
Minimum bending radius, flexible installation 12 x D  
Number of bending cycles 2000000  
Minimum bending radius, drag chain applications 10 x D  
Traversing path 5 m  
Traversing rate 4 m/s  
Acceleration 5 m/s<sup>2</sup>  
Cable weight 86 kg/km  
Outer sheath, material POC  
Material conductor insulation POC  
Conductor material Tin-plated Cu litz wires  
Nominal voltage, cable 300 V  
Test voltage Core/Core 3500 V  
Test voltage Core/Shield 2500 V  
Special properties Irradiated  
Flame resistance IEC 60332-1  
According to DIN EN 50265-2-1  
Halogen-free according to IEC 60754-1  
in accordance with DIN EN 50267-2-1  
Other resistance Good resistance to aggressive media  
Concentration of fumes in accordance with IEC 61034  
EN 50268-2  
Ambient temperature (operation) -55 °C ... 145 °C (cable, fixed installation)  
-35 °C ... 120 °C (cable, flexible installation)  
Classificati...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-5P- 5,0-BF145/M12FS SH with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.