

INDUSTRIAL COMPONENT DATA

SAC-5P- 5,0-PUR/P12FR SH 1476885 PHOENIX CONTACT

Sensor/actuator cable, 5-pole, halogen-free PUR, greyish bl..

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-5P-5,0-PUR/P12FR SH



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-5P-5,0-PUR/P12FR SH
Catalog number	1476885
Category	Sensor-actuator patch cord
Minimum order	1 Pcs
Document ID	EO-15F8F0B865
Generated	2026-08-03

Product Overview

Sensor/actuator cable, 5-pole, halogen-free PUR, greyish black RAL 7021, shielded (Advanced Shielding Technology), Elbowed female M12 Push-pull, coding: A, to free cable end, cable length: 5 m

Sensor/actuator cable, 5-pole, halogen-free PUR, greyish black RAL 7021, shielded (Advanced Shielding Technology), M12 Push-Pull angled connection female, coding: A, at free cable end, cable length: 5 m

Sensor/actuator cable, 5-pole, PUR halogen-free, black-grey RAL 7021, shielded (Advanced Shielding Technology), socket angled M12 Push-Pull, coding: A, wired with unswitched, on free end of line, cable length: 5 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Industrial Field Connectivity (IFC)

Additional Product Information

Technical dataAssemblyConnection type Push-Pull

Item propertiesProduct Type Sensor/Actuator Cable

Number of poles 5

Application Standard

Number of cable outlets 1

Shielded Yes

Coding A

Insulation properties

Surge Category II

Degree of contamination 3

Material specifications Flammability class according to UL 94 V0
Outer Jacket, Material PUR
Material Conductor bare copper wire
Electrical properties Contact resistance $\leq 5 \text{ m}\Omega$
Insulation resistance $\geq 100 \text{ M}\Omega$
Rated voltage UN 48 V AC
60 V DC
Nominal current I_N 4 A
Protective circuitry unswitched
Conductor resistance max. $58 \text{ }\Omega/\text{km}$
Mechanical properties Mechanical data
Mating cycles ≥ 100
Bending cycles maximum 10000000
Signaling Status display Yes
Status indicator available Yes
Connection data Connection technology
Connection type Push-Pull
Conductor connection
Connection type Push-Pull
Connectors Port 1
Design Socket angled M12 Push-Pull
Number of poles 5
Lock type Push-Pull
Encoding type A
Port 2
Design free end of line
Cable / Wire Cable length 5 m
PUR halogen-free black [PUR]
Dimensional drawing
Line weight 43 kg/km
UL AWM Style 20549 / 10493 (80 °C / 300 V)
Number of poles 5
Shielded Yes
Line Type PUR halogen-free black [PUR]
Conductor structure Signal cable 42x 0.10 mm
AWG signal line 22
Cable cross-section 5x 0.34 mm² (signal line)
Core diameter including insulation 1.27 mm $\pm 0.02 \text{ mm}$ (signal line)
Pipe outer diameter 5.25 mm $\pm 0.2 \text{ mm}$
Outer Jacket, Material PUR
Outer Jacket, Colour black-grey RAL 7021
Material Conductor bare copper wir...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-5P-5,0-PUR/P12FR SH with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.