

INDUSTRIAL COMPONENT DATA

SAC-5P- 5,0-PUR/P12FS SH 1476890 PHOENIX CONTACT

Sensor/actuator cable, 5-pole, halogen-free PUR, greyish bl..

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-5P-5,0-PUR/P12FS SH



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-5P-5,0-PUR/P12FS SH
Catalog number	1476890
Category	Sensor-actuator patch cord
Minimum order	1 Pcs
Document ID	EO-5548FF7E2C
Generated	2026-08-03

Product Overview

Sensor/actuator cable, 5-pole, halogen-free PUR, greyish black RAL 7021, shielded (Advanced Shielding Technology), Straight female M12 Push-pull, coding: A, to free cable end, cable length: 5 m

Sensor/actuator cable, 5-pole, halogen-free PUR, greyish black RAL 7021, shielded (Advanced Shielding Technology), M12 Push-Pull straight connection female, coding: A, to free cable end, cable length: 5 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Industrial Field Connectivity (IFC)

Additional Product Information

Technical dataassemblyConnection type Push-Pull
Item PropertiesProduct Type Sensor/Actuator Cables
Number of poles 5
application Standard
Number of Cable Outlets 1
Shielded Yes
Codification to
Insulation Properties
Surge Category li
Degree of pollution 3
Material DataFlammability class according to UL 94 V0
Outer Wrap, Material PUR

Conductive Material Naked Cu Conductor
Electrical PropertiesContact resistance $\leq 5 \text{ m}\Omega$
Insulation resistance $\geq 100 \text{ M}\Omega$
Nominal voltage UN 48 V AC
60 V DC
Nominal Current IN 4 A
Protection Circuit Unplugged
Max. Conductor Resistance $58 \text{ m}\Omega/\text{km}$
Mechanical PropertiesMechanical data
Plug Cycles ≥ 100
Max. bending cycles 10000000
SignageStatus Indication No
Available Status Indication No
Connection dataConnection technology
Connection type Push-Pull
Connecting Conductors
Connection type Push-Pull
ConnectorsConnection 1
Construction Straight Female M12 Push-pull
Number of poles 5
Locking system Push-pull
Encoding Type to
Connection 2
Construction Free Cable End
Cable/LineCable length 5 m
Halogen-free PUR Black [PUR]
Dimension Scheme
Cable Weight 43 kg/km
UL AWM Style 20549 / 10493 (80°C/300V)
Number of poles 5
Shielded Yes
Cable type Halogen-free PUR Black [PUR]
Conductor Construction Signal Cable 42x 0.10 mm
AWG Signal Line 22
Line Section $5 \times 0.34 \text{ mm}^2$ (signal conductor)
Conductor diameter incl. insulation $1.27 \text{ mm} \pm 0.02 \text{ mm}$ (signal conductor)
Cable Outer Diameter $5.25 \text{ mm} \pm 0.2 \text{ mm}$
Outer Wrap, Material PUR
Outer Wrap, Color greyish black RAL 7021
Conductive Mate...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-5P-5,0-PUR/P12FS SH with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.