

INDUSTRIAL COMPONENT DATA

SAC-5P- 6,0-186/M12FR 1570775 PHOENIX CONTACT

Sensor/actuator cable

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-5P-6,0-186/M12FR



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-5P-6,0-186/M12FR
Catalog number	1570775
Category	Sensor-actuator patch cord
Minimum order	50 Pcs
Document ID	EO-20911F8E37
Generated	2026-08-06

Product Overview

Sensor/actuator cable

Sensor/actuator cable, 5-pole, PUR, greyish black RAL 7021, free cable end, to Angled connection female M12, coding: A, cable length: 6 m

Sensor/actuator cable, 5-position, PUR, black-gray RAL 7021, free cable end, on Socket angled M12, coding: A, cable length: 6 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Industrial Field Connectivity (IFC)

Additional Product Information

Technical dataProduct propertiesProduct type Sensor/actuator cable

Number of positions 5

No. of cable outlets 1

Shielded no

Coding A

Insulation characteristics

Overvoltage category II

Degree of pollution 3

Material specificationsFlammability rating according to UL 94 HB

Seal material NBR

Material of grip body TPU, hardly inflammable, self-extinguishing

Contact material CuSn
Contact surface material Ni/Au
Contact carrier material TPU GF
Material for screw connection Zinc die-cast, nickel-plated
Electrical propertiesInsulation resistance $\geq 100 \text{ M}\Omega$
Nominal voltage UN 48 V AC
60 V DC
Nominal current IN 4 A
Mechanical propertiesMechanical data
Insertion/withdrawal cycles ≥ 100
SignalingStatus display no
Status display present No
ConnectorConnection 1
Type free cable end
Connection 2
Type Socket angled M12
Number of positions 5
Coding type A
Cable/lineCable length 6 m
PUR POWER 0.75 mm² black [186]
Dimensional drawing
Cable weight 67 kg/km
Number of positions 5
Shielded no
Cable type PUR POWER 0.75 mm² black [186]
Conductor structure signal line 42x 0.15 mm
AWG signal line 18
Conductor cross section 5x 0.75 mm² (power line)
Wire diameter incl. insulation 1.7 mm $\pm 0.05 \text{ mm}$
External cable diameter 6.30 mm $\pm 0.2 \text{ mm}$
Outer sheath, material PUR
External sheath, color black-gray RAL 7021
Conductor material Bare Cu litz wires
Material wire insulation PVC
Single wire, color brown, white, blue, black, gray
Thickness, insulation $\geq 0.23 \text{ mm}$ (Core insulation)
 $\geq 0.76 \text{ mm}$ (Outer cable sheath)
Overall....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-5P-6,0-186/M12FR with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.