

INDUSTRIAL COMPONENT DATA

SAC-5P- 7,5-PUR/M12FS LUE 1536787 PHOENIX CONTACT Sensor/Actuator Cable, 5-pole, free cable end, to Straight..

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-5P-7,5-PUR/M12FS LUE



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-5P-7,5-PUR/M12FS LUE
Catalog number	1536787
Category	Sensor-actuator patch cord
Minimum order	50 Pcs
Document ID	EO-E74B720AF2
Generated	2026-08-05

Product Overview

Sensor/Actuator Cable, 5-pole, free cable end, to Straight female M12, coding: A, cable length: 7.5 m

Sensor/actuator cable, 5-pole, halogen-free PUR, greyish black RAL 7021, free cable end, to M12 straight connection female, coding: A, cable length: 7.5 m

Sensor/actuator cable, 5-position, free cable end, on Socket straight M12, coding: A, cable length: 7.5 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Field Connectivity (IFC)
--------------	---

Additional Product Information

Technical dataProduct propertiesProduct type Sensor/actuator cable

Number of positions 5

No. of cable outlets 1

Shielded no

Coding A

Insulation characteristics

Overvoltage category II

Degree of pollution 3

Material specificationsFlammability rating according to UL 94 HB

Material of grip body TPU, hardly inflammable, self-extinguishing

Contact material CuSn

Contact surface material Ni/Au

Contact carrier material TPU GF
Material for screw connection Zinc die-cast, nickel-plated
Electrical propertiesContact resistance $\leq 5 \text{ m}\Omega$?
Insulation resistance $\geq 100 \text{ M}\Omega$?
Nominal voltage UN 48 V AC
60 V DC
Nominal current IN 4 A
Mechanical propertiesMechanical data
Insertion/withdrawal cycles ≥ 100
SignalingStatus display No
Status display present No
ConnectorConnection 1
Type free cable end
Connection 2
Type Socket straight M12
Number of positions 5
Coding type A
Cable/lineCable length 7.5 m
PUR halogen-free black [PUR]
Dimensional drawing
Shielded no
UL AWM Style 20549
Cable weight 33 kg/km
Cable type PUR halogen-free black
Cable type (abbreviation) PUR
External cable diameter 4.55 mm $\pm 0.15 \text{ mm}$
Outer sheath, material PUR
External sheath, color black-gray RAL 7021
Conductor material Bare Cu litz wires
Conductor structure signal line 42x 0.10 mm
AWG signal line 22
Conductor cross section 5x 0.34 mm² (Signal line)
Material wire insulation PP
Thickness, insulation approx. 0.5 mm
Wire diameter incl. insulation 1.27 mm 0.05 mm (Signal line)
Single wire, color brown, white, blue, black, green-yellow....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-5P-7,5-PUR/M12FS LUE with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.