

INDUSTRIAL COMPONENT DATA

SAC-5P-M12FS/0,6-115/M12FS 1549427 PHOENIX CONTACT

Sensor/actuator cable, 5-pole, halogen-free PUR, greyish ..

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-5P-M12FS/0,6-115/M12FS



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-5P-M12FS/0,6-115/M12FS
Catalog number	1549427
Category	Sensor-actuator patch cord
Minimum order	100 Pcs
Document ID	EO-9C5CA9E14F
Generated	2026-08-06

Product Overview

Sensor/actuator cable, 5-pole, halogen-free PUR, greyish black RAL 7021, Straight connector M12, coding: A, to Straight female M12, coding: A, cable length: 0.6 m

Sensor/actuator cable, 5-pole, halogen-free PUR, greyish black RAL 7021, M12 straight male connector, coding: A, A M12 straight connection female, coding: A, cable length: 0.6 m

Sensor/actuator cable, 5-position halogen-free, Plug straight M12, coding: A, on Socket straight M12, coding: A, cable length: 0.6 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Industrial Field Connectivity (IFC)

Additional Product Information

Technical dataProduct propertiesProduct type Sensor/actuator cable

Number of positions 5

Shielded no

Insulation characteristics

Overvoltage category II

Degree of pollution 3

Material specificationsFlammability rating according to UL 94 HB

Seal material NBR

Material of grip body TPU, hardly inflammable, self-extinguishing

Contact material CuSn

Contact surface material Ni/Au
Contact carrier material TPU GF
Material for screw connection Zinc die-cast, nickel-plated
Electrical propertiesNominal voltage UN 48 V AC
60 V DC
Nominal current IN 4 A
Mechanical propertiesMechanical data
Insertion/withdrawal cycles ≥ 100
SignalingStatus display No
Status display present No
ConnectorConnection 1
Type Plug straight M12
Number of positions 5
Coding type A
Connection 2
Type Socket straight M12
Number of positions 5
Coding type A
Cable/lineCable length 0.6 m
PUR, black, 5th conductor gray [115]
Dimensional drawing
Cable weight 35 kg/km
UL AWM Style 20549 / 10493 (80°C/300 V)
Number of positions 5
Shielded no
Cable type PUR, black, 5th conductor gray [115]
Conductor structure signal line 42x 0.10 mm
AWG signal line 22
Conductor cross section 5x 0.34 mm²
Wire diameter incl. insulation 1.27 mm ± 0.02 mm
External cable diameter 5 mm ± 0.15 mm
Outer sheath, material PUR
External sheath, color black-gray RAL 7021
Conductor material Bare Cu litz wires
Material, filler PP
Material wire insulation PP
Single wire, color brown, white, blue, black, gray
Thickness, insulation ≥ 0.21 mm
Thickness, outer she...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-5P-M12FS/0,6-115/M12FS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.