

INDUSTRIAL COMPONENT DATA

SAC-5P-M12MR/1,94PUR/M12FS 2X4 1413021 PHOENIX

CONTACT Sensor/actuator cable

SAC-5P-M12MR/1,94PUR/M12FS 2X4 ..

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-5P-M12MR/1,94PUR/M12FS 2X4



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-5P-M12MR/1,94PUR/M12FS 2X4
Catalog number	1413021
Category	Sensor-actuator patch cord
Minimum order	50 Pcs
Document ID	EO-1D823B2723
Generated	2026-08-06

Product Overview

Sensor/actuator cable - SAC-5P-M12MR/1,94PUR/M12FS 2X4 - 1413021

Sensor/actuator cable, 5-pole, halogen-free PUR, greyish black RAL 7021, Angled male connector M12, coding: coded A, a Straight connection female M12, coding: coded A, cable length: 1.94 m, Customer variant

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Field Connectivity (IFC)
--------------	---

Additional Product Information

Sensor/actuator cable, 5-position, PUR halogen-free, black-gray RAL 7021, Plug angled M12, A-coded, on Socket straight M12, A-coded, cable length: 1.94 m, Customer version

Key Commercial Data

Orderkey 1413021

Packing unit 1

GTIN 4046356981682

Custom tariff number 85444290

Dimensions

Length of cable 1.94 m

Ambient conditions

Ambient temperature (operation) -25 °C ... 90 °C (Plug / socket)

General

Rated current at 40°C 4 A

Rated voltage 48 V AC

60 V DC

Number of positions 5

Insulation resistance $\geq 100 \text{ M}\Omega$

Coding A - standard

Standards/regulations M12 connector IEC 61076-2-101

Status display No

Protective circuit/component unwired

Overvoltage category II

Degree of pollution 3

Insertion/withdrawal cycles ≥ 100 **Material**

Flammability rating according to UL 94 HB

Contact material CuSn

Contact surface material Ni/Au

Contact carrier material TPU GF

Material of grip body TPU, hardly inflammable, self-extinguishing

Material, knurls Zinc die-cast, nickel-plated

Sealing material NBR

Standards and Regulations

Standard designation M12 connector

Standards/regulations IEC 61076-2-101

Flammability rating according to UL 94 HB

Cable

Cable type PUR halogen-free black

Cable type (abbreviation) PUR

UL AWM style 20549

Conductor cross section $5 \times 0.34 \text{ mm}^2$ (Signal line)

AWG signal line 22

Conductor structure signal line $42 \times 0.10 \text{ mm}$ Core diameter including insulation $1.27 \text{ mm} \pm 0.02 \text{ mm}$ (Signal line)Thickness, insulation approx. 0.5 mm

Wire colors brown, white, blue, black, green-yellow

External sheath,....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-5P-M12MR/1,94PUR/M12FS 2X4 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.