

INDUSTRIAL COMPONENT DATA

SAC-5P-M12MS/0,3-PUR/AD-2L 1439609 PHOENIX CONTACT

Cable for sensors/actuators 5-pin, male Connector straigh..

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-5P-M12MS/0,3-PUR/AD-2L



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-5P-M12MS/0,3-PUR/AD-2L
Catalog number	1439609
Category	Sensor-actuator patch cord
Minimum order	1 Pcs
Document ID	EO-77CC0F76CE
Generated	2026-08-06

Product Overview

Cable for sensors/actuators 5-pin, male Connector straight M12, a coded, On valve Connector AD (pressure switch), with 2 LEDs, cable length: 0.3 m

Sensor/actuator cable, 5-pole, M12 straight connector, coding: A, to AD valve connectors (Druckschalter), with 2 LEDs, cable length: 0.3 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Industrial Field Connectivity (IFC)

Additional Product Information

Cable for sensor / actuator, 5-pin,, PUR halogen-free, dark gray RAL 7021, Plug straight M12, A-coding, to Plug type AD to the solenoid valve (pressure switch), with 2 led, cable length: 0.3 m

Commercial data

Order code One million four hundred thirty nine thousand six hundred nine

Packaging unit 1 stk

GTIN Four trillion forty six billion three hundred fifty six million four hundred eighty nine thousand four hundred fifty four

Weight/PCs (without packing) 47,500 GRM

Dimensions

Cable length 0.3 m

General information

Rated voltage 24 V AC

24 V DC

Poles Five

Standards/normative documents M12 connector IEC 61076-2-101

Connectors for valve EN 175301-803

Cycles installation ≥ 100

Standards and regulations

The designation of the standard M12 Connector

Standards / normative documents IEC 61076-2-101

The designation of the standard Connectors for valves

Standards / normative documents EN 175301-803

Cable

Cable type PUR zero halogen black

Cable type (short designation) polyurethane

Symbol cable Li9Y11Y-HF

UL AWM Style Twenty thousand five hundred forty nine

Wire cross-section $5 \times 0,5 \text{ mm}^2$

AWG signal line Twenty

Cable design, the signal line $28 \times 0.15 \text{ mm}$

Conductor diameter incl. insulation $1.5 \text{ mm} \pm 0.05 \text{ mm}$ (Signal wire)

Color lived black 1, black 2, black 3, black 4, green/yellow

General twisting 5 lived in the strand

Outer shell, color dark gray RAL 7021

Outer diameter of cable $D 5.3 \text{ mm} \pm 0.02 \text{ mm}$

Minimum bending radius when laying hard 26.5 mm

Minimum bending radius, when the movable space...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-5P-M12MS/0,3-PUR/AD-2L with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.