

INDUSTRIAL COMPONENT DATA

SAC-5P-M12MS/0,3-PVC/FS VA 3/4 1410525 PHOENIX CONTACT Sensor/actuator cable SAC-5P-M12MS/0,3-PVC/FS VA 3/4 ..

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-5P-M12MS/0,3-PVC/FS VA 3/4



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-5P-M12MS/0,3-PVC/FS VA 3/4
Catalog number	1410525
Category	Sensor-actuator patch cord
Minimum order	50 Pcs
Document ID	EO-9E883FA60E
Generated	2026-08-06

Product Overview

Sensor/actuator cable - SAC-5P-M12MS/0,3-PVC/FS VA 3/4 - 1410525

Sensor/actuator cable, 5-pole, PVC, black RAL 9005, Straight male connector M12, coding: A, to Straight connection female M12, coding: A, cable length: 0.3 m, Special connection, Pin mapping: 1-1; 2-2; 3-4; 4-3; 5-5

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Industrial Field Connectivity (IFC)

Additional Product Information

Sensor/actuator cable, 5-position, PVC, black RAL 9005, Plug straight M12, A-coded, on Socket straight M12, A-coded, cable length: 0.3 m, Special wiring, Pin assignment: 1-1; 2-2; 3-4; 4-3; 5-5

Key Commercial Data

Orderkey 1410525

Packing unit 1

GTIN 4046356899185

Custom tariff number 85444290

Dimensions

Length of cable 0.3 m

General

Rated current at 40°C 4 A

Rated voltage 48 V AC
60 V DC
Number of positions 5
Insulation resistance $\geq 100 \text{ M}\Omega$
Coding A - standard
Status display No
Overvoltage category II
Degree of pollution 3
Insertion/withdrawal cycles ≥ 100
Material
Flammability rating according to UL 94 HB
Contact material CuSn
Contact surface material Ni/Au
Contact carrier material TPU GF
Material of grip body TPU, hardly inflammable, self-extinguishing
Material, knurls Stainless steel
Sealing material NBR
Pin assignment
Contact | Color (signal designation) | Contact (optional) 1 (M12 plug) | BN | 1 (M12 socket)
2 (M12 plug) | WH | 2 (M12 socket)
3 (M12 plug) | BK | 4 (M12 socket)
4 (M12 plug) | BU | 3 (M12 socket)
5 (M12 plug) | GN/YE | 5 (M12 socket)
Standards and Regulations
Flame resistance As per UL-Style 2464
Resistance to oil in accordance with DIN EN 60811-2-1
Flammability rating according to UL 94 HB
Cable
Cable type PVC black
Cable type (abbreviation) PVC
Cable abbreviation LiYY
UL AWM style 2464 / 1729 (80°C/300 V)
Conductor cross section $5 \times 0.34 \text{ mm}^2$ (Signal line)
AWG signal line 22
Conductor structure signal line $19 \times 0.15 \text{ mm}$
Core diameter including insulation 1....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-5P-M12MS/0,3-PVC/FS VA 3/4 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.