

INDUSTRIAL COMPONENT DATA

SAC-5P-M12MS/0,6-PUR/AD-2L 1439573 PHOENIX CONTACT

Sensor/actuator cable SAC-5P-M12MS/0,6-PUR/AD-2L 1439573

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-5P-M12MS/0,6-PUR/AD-2L



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-5P-M12MS/0,6-PUR/AD-2L
Catalog number	1439573
Category	Sensor-actuator patch cord
Minimum order	1 Pcs
Document ID	EO-59DE418E1D
Generated	2026-08-04

Product Overview

Sensor/actuator cable - SAC-5P-M12MS/0,6-PUR/AD-2L - 1439573

Sensor/actuator cable, 5-pole halogen-free, M12 straight connector, coding: A, with 2 LEDs, to AD valve connectors (Druckschalter), with 2 LEDs, cable length: 0.6 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Industrial Field Connectivity (IFC)

Additional Product Information

Sensor/actuator cable, 5-position, PUR halogen-free, black-gray RAL 7021, Plug straight M12, A-coded, on Valve connector AD (pressure switch), with 2 LEDs, cable length: 0.6 m

Key Commercial Data

Orderkey 1439573

Packing unit 1

GTIN 4046356489423

Custom tariff number 85444290

Dimensions

Length of cable 0.6 m

Ambient conditions

Ambient temperature (operation) -25 °C ... 90 °C (Plug / socket)

-20 °C ... 85 °C (valve plug)

Degree of protection IP65

IP67

General

Rated current at 40°C 4 A

Rated voltage 24 V AC

24 V DC

Number of positions 5

Insulation resistance $\geq 100 \text{ M}\Omega$

Coding A - standard

Standards/regulations M12 connector IEC 61076-2-101

Valve connector EN 175301-803

Status display 2 LEDs

Protective circuit/component unwired

Overvoltage category II

Degree of pollution 3

Insertion/withdrawal cycles ≥ 100 (M12 connector)

Torque 0.6 Nm (Valve connector)

0.4 Nm (M12 connector)

Material

Flammability rating according to UL 94 V0

Contact material CuSn

Contact surface material Ni/Au

Contact carrier material TPU GF

Material of grip body TPU, hardly inflammable, self-extinguishing

Valve plug contact material CuSn

Valve plug contact surface material Ag

Valve plug contact insert material PBT

Material housing valve plug PBT

Material, knurls Zinc die-cast, nickel-plated

Sealing material TPU (Seal molded)

Standards and Regulations

Standard designation M12 connector

Standards/regulations IEC 61076-2-101

Standard designation Valve connector

Standards/regulations EN 175301-803

Flammability rati...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-5P-M12MS/0,6-PUR/AD-2L with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.