

INDUSTRIAL COMPONENT DATA

SAC-5P-M12MS/ 1,0-802/M12FS 1454574 PHOENIX CONTACT

Cable for sensors/actuators, 5-pole, PUR halogen-free, r..

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-5P-M12MS/ 1,0-802/M12FS



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-5P-M12MS/ 1,0-802/M12FS
Catalog number	1454574
Category	Sensor-actuator patch cord
Minimum order	1 Pcs
Document ID	EO-CF0BE8EE4A
Generated	2026-08-04

Product Overview

Cable for sensors/actuators, 5-pole, PUR halogen-free, resistant to welding spatter, highly flexible, gray RAL 7001, Plug straight M12, coded A, A connection socket straight M12, coded, cable length: 1 m

Sensor/actuator cable, 5-pole, halogen-free, solder-resistant, highly flexible, grey RAL 7001, M12 straight male connector, encoding: A, to M12 straight connection female, encoding: A, cable length: 1 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Field Connectivity (IFC)
--------------	---

Additional Product Information

Sensor/actuator cable, 5-pole, PUR halogen-free, weld-spark-resistant, highly flexible, grey RAL 7001, plug straight M12, A-coded, on socket straight M12, A-coded, cable length: 1 m

Commercial data

Order key 1454574

Packaging unit 1 PC

Sales key C1 - Sensor-Actuator Cable

Note Made-to-order production (no returns)

GTIN 4046356578264

Weight per piece (excluding packaging) 55,700 g

Weight per piece (including packaging) 57,900 g

Customs tariff number 85444290

Country of origin PL (Poland)

Dimensions

Cable length 1 m

Environmental conditions

Ambient temperature (operating) -25 °C ... 90 °C (plug/socket)

Degree of protection IP65

IP67

IP68

General

Rated current at 40 °C 4 A

Rated voltage 48 V AC

60 V DC

Number of poles 5

Insulation resistance $\geq 100 \text{ M}\Omega$

Coding A - Standard

Status display Yes

Surge Category II

Degree of contamination 3

Material

Flammability class according to UL 94 HB

Material Contact CuSn

Contact surface material Ni/Au

Material Contact Carrier TPU GF

Material Handle Body TPU, flame retardant, self-extinguishing

Material Knurling Die-cast zinc, nickel-plated

Material Gasket NBR

Standards and regulations

Flammability class according to UL 94 HB

Management

Note Due to the very robust outer sheath, this cable can only be stripped in 5 cm steps.

Cable Type PUR, halogen-free, highly flexible, weld-spark-resistant, grey

Cable type (characters) 802

Cable abbreviations Li12Y11Y-HF

Conductor cross-section $5 \times 0.34 \text{ mm}^2$ (signal line)

AWG signal line 22

Conductor structure Sign...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-5P-M12MS/ 1,0-802/M12FS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.