

INDUSTRIAL COMPONENT DATA

SAC-5P-M12MS/ 1,0-PUR/M12FR VW 1693940 PHOENIX CONTACT Sensor/actuator cable

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-5P-M12MS/ 1,0-PUR/M12FR VW



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-5P-M12MS/ 1,0-PUR/M12FR VW
Catalog number	1693940
Category	Sensor-actuator patch cord
Minimum order	5 Pcs
Document ID	EO-D5CD09ADFC
Generated	2026-08-05

Product Overview

Sensor/actuator cable

Sensor/actuator cable, 5-pole, halogen-free PUR, irradiation-crosslinked, orange RAL 2003, M12 straight male connector, coding: A, to M12 angled connection female, coding: A, cable length: 1 m, Customer-specific variants

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Industrial Field Connectivity (IFC)

Additional Product Information

Key Commercial Data

Orderkey 1693940

Packing unit 5 pc

Minimum order quantity 5 pc

Note Made to Order (non-returnable)

GTIN 4017918481735

Weight per Piece (excluding packing) 60.400 g

Custom tariff number 85444290

Country of origin PL (Poland)

Dimensions

Length of cable 1 m

Ambient conditions

Ambient temperature (operation) -25 °C ... 90 °C (Plug / socket)

Degree of protection IP65
IP67
IP68
General
Rated current at 40°C 4 A
Rated voltage 48 V AC
60 V DC
Number of positions 5
Insulation resistance $\geq 100 \text{ M}\Omega$
Coding A - standard
Status display No
Overvoltage category II
Degree of pollution 3
Insertion/withdrawal cycles ≥ 100
Material
Flammability rating according to UL 94 HB
Contact material CuSn
Contact surface material Ni/Au
Contact carrier material TPU GF
Material of grip body TPU, hardly inflammable, self-extinguishing
Material, knurls Zinc die-cast, nickel-plated
Sealing material NBR
Standards and Regulations
Flammability rating according to UL 94 HB
Cable
Cable type PUR irradiated halogen-free orange
Cable type (abbreviation) 150
Cable abbreviation D12YSL11X-JB
Conductor cross section 4x 0.34 mm² (Signal line)
1x 0.5 mm² (PE connection)
AWG signal line 22
AWG power supply 20
Conductor structure signal line 42x 0.10 mm
Conductor structure, voltage supply 24x 0.15 mm
Wire colors Brown, blue, black, white, green/yellow
Overall twist 5 cores, twisted
External sheath, color orange RAL 2003
External cable diameter D 5.2 mm $\pm 0.2 \text{ mm}$
Smallest bending radius, fixed installation min...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-5P-M12MS/ 1,0-PUR/M12FR VW with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.