

INDUSTRIAL COMPONENT DATA

SAC-5P-M12MS/10,0-927/M12FS VA 1402950 PHOENIX CONTACT 5-pos. cable, black PVC, shielded, shielded plug, str..

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-5P-M12MS/10,0-927/M12FS VA



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-5P-M12MS/10,0-927/M12FS VA
Catalog number	1402950
Category	Sensor-actuator patch cord
Minimum order	50 Pcs
Document ID	EO-3D4A3DC77E
Generated	2026-08-05

Product Overview

5-pos. cable, black PVC, shielded, shielded plug, straight M12, A-coded, on shielded socket, straight M12, A-coded with VA knurl, length: 10 m

5-pole cable, black shielded PVC, straight shielded maleM12, codif. A, in female connection. shielded straight M12, codif. A with knurling VA, length: 10 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Field Connectivity (IFC)
--------------	---

Additional Product Information

Key Commercial Data

Orderkey 1402950

Packing unit 1 pc

Minimum order quantity 50 pc

GTIN 4046356637688

Weight per Piece (excluding packing) 0.000 g

Custom tariff number 85444290

Country of origin PL (Poland)

Dimensions

Cable

Classifications

General

Environmental Product Compliance

Dimensions

Length of cable 10 m

[Back to top](#)General

Rated voltage 48 V AC

60 V DC

Number of positions 5

[Back to top](#)Cable

Cable type DeviceNet™

Cable type (abbreviation) 927

UL AWM style 2464 (80°C/300 V)

Conductor cross section 2x 0.34 mm² (Signal line)

2x 0.34 mm² (Power supply)

1x 0.38 mm² (Drain wire)

AWG signal line 22

AWG power supply 22

Conductor structure signal line 44x 0.10 mm

Conductor structure, voltage supply 44x 0.10 mm

Core diameter including insulation 2.55 mm (Signal line)

1.37 mm (Power supply)

Thickness, insulation ≥ 0.3 mm (Wire insulation power supply)

Wire colors Red-black, blue-white

Twisted pairs 2 cores to the pair

Type of pair shielding Aluminum-lined polyester foil

Overall twist 2 pairs with filler elements, around a drain wire in the center to the core

Shielding Tinned copper braided shield

Optical shield covering 85 %

External sheath, color black

Outer sheath thickness ≥ 1 mm

External cable diameter D 8.3 mm ± 0.3 mm

Minimum bending radius, fixed installation 4 x D

Minimum bending radius, flexible installation 8 x D

Cable weight 83 kg/km

Outer sheath, material PVC

Material conductor insulation Foamed PP (Signal line)

PVC (Power supply)

Conductor material Tin-plated Cu litz...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-5P-M12MS/10,0-927/M12FS VA with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.