

INDUSTRIAL COMPONENT DATA

SAC-5P-M12MS/10PVC/M12FS SH VA 1418851 PHOENIX CONTACT Sensor/actuator cable

SAC-5P-M12MS/10PVC/M12FS SH VA ..

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-5P-M12MS/10PVC/M12FS SH VA



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-5P-M12MS/10PVC/M12FS SH VA
Catalog number	1418851
Category	Sensor-actuator patch cord
Minimum order	50 Pcs
Document ID	EO-23F67A99F1
Generated	2026-08-05

Product Overview

Sensor/actuator cable - SAC-5P-M12MS/10PVC/M12FS SH VA - 1418851

Sensor/actuator cable, 5-pole, PVC, black RAL 9005, shielded, Straight connector M12, coding: A, to Straight female M12, cable length: 10 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > Industrial Field Connectivity (IFC)**

Additional Product Information

Sensor/actuator cable, 5-position, PVC, black RAL 9005, shielded, cable length: 10 m

Key Commercial Data

Orderkey 1418851

Packing unit 1

GTIN 4055626152264

Custom tariff number 85444290

Dimensions

Length of cable 10 m

General

Rated current at 40°C 4 A

Rated voltage 48 V AC

60 V DC
Number of positions 5
Coding A - standard
Status display No
Overvoltage category II
Degree of pollution 3
Material
Flammability rating according to UL 94 HB
Contact material CuSn
Contact surface material Ni/Au
Contact carrier material TPU GF
Material of grip body TPU, hardly inflammable, self-extinguishing
Material, knurls Zinc die-cast, nickel-plated
Sealing material NBR
Standards and Regulations
Flammability rating according to UL 94 HB
Cable
Cable type PVC black
Cable type (abbreviation) PVC
Conductor cross section 5x 0.34 mm² (Signal line)
AWG signal line 22
Conductor structure signal line 42x 0.10 mm
Core diameter including insulation 1.35 mm ±0.02 mm
Thickness, insulation ≥ 0.23 mm (Core insulation)
≥ 0.76 mm (Outer cable sheath)
Wire colors Brown, white, blue, black, gray
Overall twist 5 wires around filler to the core
Shielding Tinned copper braided shield
Optical shield covering 85 %
External sheath, color black RAL 9005
External cable diameter D 5.9 mm ±0.2 mm
Cable weight 55 kg/km
Outer sheath, material PVC
Material, filler PVC
Material conductor insulation PVC
Conductor material Bare Cu litz wires
Insulation resistance ≥ 10 MΩ·km (at 20 °C)
Conductor resistance ≤ 58 Ω/km (at 20 °C)
Nomi...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-5P-M12MS/10PVC/M12FS SH VA with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.