

INDUSTRIAL COMPONENT DATA

SAC-5P-M12MS/ 1,5-PUR SH5 1402231 PHOENIX CONTACT

Sensor/actuator cable

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-5P-M12MS/ 1,5-PUR SH5



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-5P-M12MS/ 1,5-PUR SH5
Catalog number	1402231
Category	Sensor-actuator patch cord
Minimum order	50 Pcs
Document ID	EO-3FDE541158
Generated	2026-08-05

Product Overview

Sensor/actuator cable

Sensor/actuator cable, 5-pole, halogen-free PUR, greyish black RAL 7021, shielded, M12 straight male connector, coding: A, to free cable end, cable length: 1.5 m

Sensor/actuator cable, 5-position, PUR halogen-free, black-gray RAL 7021, shielded, Plug straight M12, coding: A, on free cable end, cable length: 1.5 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Field Connectivity (IFC)
--------------	---

Additional Product Information

Technical dataProduct propertiesProduct type Sensor/actuator cable

Number of positions 5

No. of cable outlets 1

Shielded yes

Coding A

Insulation characteristics

Overvoltage category II

Degree of pollution 3

Material specificationsFlammability rating according to UL 94 HB

Seal material NBR

Material of grip body TPU, hardly inflammable, self-extinguishing

Contact material CuSn
Contact surface material Ni/Au
Contact carrier material TPU GF
Material for screw connection Zinc die-cast, nickel-plated
Electrical propertiesInsulation resistance $\geq 100 \text{ M}\Omega$
Nominal voltage UN 48 V AC
60 V DC
Nominal current IN 4 A
Mechanical propertiesMechanical data
Insertion/withdrawal cycles ≥ 100
SignalingStatus display no
Status display present No
ConnectorConnection 1
Type Plug straight M12
Number of positions 5
Coding type A
Connection 2
Type free cable end
Cable/lineCable length 1.5 m
PUR halogen-free black [PUR]
Dimensional drawing
Cable weight 36 kg/km
UL AWM Style 20549 / 10493 (80°C/300 V)
Number of positions 4
Shielded yes
Cable type PUR halogen-free black [PUR]
Conductor structure signal line 42x 0.10 mm
AWG signal line 22
Conductor cross section 4x 0.34 mm² (Signal line)
Wire diameter incl. insulation 1.27 mm $\pm 0.02 \text{ mm}$ (Signal line)
External cable diameter 4.95 mm $\pm 0.2 \text{ mm}$
Outer sheath, material PUR
External sheath, color black-gray RAL 7021
Conductor material Bare Cu litz wires
Material wire insulation PP
Single wire, color brown, white, blue, black
Thickness, insulation $\geq 0.21 \text{ mm}$
Thicknes...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-5P-M12MS/ 1,5-PUR SH5 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.