

INDUSTRIAL COMPONENT DATA

SAC-5P-M12MS/15,0-923/M12FS 1413290 PHOENIX CONTACT

Bus system cable SAC-5P-M12MS/15,0-923/M12FS 1413290

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-5P-M12MS/15,0-923/M12FS



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-5P-M12MS/15,0-923/M12FS
Catalog number	1413290
Category	Sensor-actuator patch cord
Minimum order	25 Pcs
Document ID	EO-D178D32110
Generated	2026-08-05

Product Overview

Bus system cable - SAC-5P-M12MS/15,0-923/M12FS - 1413290

Bus system cable, CANopen®, DeviceNet™, 5-pole halogen-free, shielded, M12 straight connector, coding: A SPEEDCON, a Straight female M12, coding: A SPEEDCON, cable length: 15 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Field Connectivity (IFC)
--------------	---

Additional Product Information

Bus system cable, CANopen®, DeviceNet™, 5-position, PUR halogen-free, silver-gray RAL 7001, shielded, Plug straight M12 SPEEDCON, A-coded, on Socket straight M12 SPEEDCON, A-coded, cable length: 15 m

Key Commercial Data

Orderkey 1413290

Packing unit 1

GTIN 4046356995696

Custom tariff number 85444290

Dimensions

Length of cable 15 m

General

Rated current at 40°C 4 A

Rated voltage 48 V AC

60 V DC

Number of positions 5
Insulation resistance $\geq 100 \text{ M}\Omega$
Coding A - standard
Signal type/category CANopen®
DeviceNet™
Status display No
Overvoltage category II
Degree of pollution 3
Material
Flammability rating according to UL 94 HB
Contact material CuSn
Contact surface material Ni/Au
Contact carrier material TPU GF
Material of grip body TPU, hardly inflammable, self-extinguishing
Material, knurls Zinc die-cast, nickel-plated
Sealing material NBR
Standards and Regulations
Flammability rating according to UL 94 HB
Cable
Cable type CAN Bus/DeviceNet drop cable
Cable type (abbreviation) 923
UL AWM style 21198 (80°C/300 V)
Cable structure 2xAWG24/19+2xAWG22/19
Conductor cross section 2x 0.25 mm² (Data cable)
2x 0.34 mm² (Power supply)
1x 0.34 mm² (Drain wire)
AWG signal line 24
AWG power supply 22
Conductor structure signal line 19x 0.13 mm
Conductor structure, voltage supply 19x 0.15 mm
Core diameter including insulation 1.95 mm $\pm 0.05 \text{ mm}$ (Data cable)
1.4 mm $\pm 0.05 \text{ mm}$ (Power supply)
Wire colors Red-black, blue-white
Twisted pairs 2 cores to the pair
Type of pair shielding Plastic-coated aluminum...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-5P-M12MS/15,0-923/M12FS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.