

INDUSTRIAL COMPONENT DATA

SAC-5P-M12MS/ 2,0-802/M12FR-3L 1454493 PHOENIX CONTACT Sensor/actuator cable

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-5P-M12MS/ 2,0-802/M12FR-3L



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-5P-M12MS/ 2,0-802/M12FR-3L
Catalog number	1454493
Category	Sensor-actuator patch cord
Minimum order	1 Pcs
Document ID	EO-1941DB04AC
Generated	2026-08-05

Product Overview

Sensor/actuator cable

Sensor/actuator cable, 5-pole, halogen-free, solder-resistant, highly flexible, grey RAL 7001, M12 straight male connector, coding: A-coded, to M12 angled connection female, coding: A-coded, with 3 LEDs, cable length: 2 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Industrial Field Connectivity (IFC)

Additional Product Information

Key Commercial Data

Orderkey 1454493

Packing unit 1

GTIN 4046356578202

Custom tariff number 85444290

Dimensions

Length of cable 2 m

Ambient conditions

Ambient temperature (operation) -25 °C ... 90 °C (Plug / socket)

Degree of protection IP65

IP67

IP68

General

Rated current at 40°C 4 A

Rated voltage 24 V

24 V DC

Number of positions 5

Insulation resistance $\geq 100 \text{ M}\Omega$

Coding A - standard

Status display 3 LEDs

Overvoltage category II

Degree of pollution 3

Material

Flammability rating according to UL 94 HB

Contact material CuSn

Contact surface material Ni/Au

Contact carrier material TPU GF

Material of grip body TPU, hardly inflammable, self-extinguishing

Material, knurls Zinc die-cast, nickel-plated

Sealing material NBR

Standards and Regulations

Flammability rating according to UL 94 HB

Cable

Note Due to the extremely robust outer sheath, this cable should only be stripped in 5 cm increments.

Cable type PUR, halogen-free, highly stranded, resistant to welding sparks, gray

Cable type (abbreviation) 802

Cable abbreviation Li12Y11Y-HF

Conductor cross section $5 \times 0.34 \text{ mm}^2$ (Signal line)

AWG signal line 22

Conductor structure signal line $42 \times 0.10 \text{ mm}$

Core diameter including insulation $1.3 \text{ mm} \pm 0.05 \text{ mm}$ (Signal line)

Wire colors Black, brown, blue, white, green/yellow

Overall twist 5 wires around filler to the core

External sheath, color gray RAL 7001

External cable diameter $D 5.1 \text{ mm} \pm 0.2 \text{ mm}$

Minimum bending radius, fixed installation $5 \times D$

Minimum bending radius, flexible installation $5 \times D$

N...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-5P-M12MS/ 2,0-802/M12FR-3L with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.