

INDUSTRIAL COMPONENT DATA

SAC-5P-M12MS/3,2-PUR/M12FS VA 1534116 PHOENIX CONTACT Sensor/Actuator Cable, 5-Pole, M12 Straight Connector,...

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-5P-M12MS/3,2-PUR/M12FS VA



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-5P-M12MS/3,2-PUR/M12FS VA
Catalog number	1534116
Category	Sensor-actuator patch cord
Minimum order	50 Pcs
Document ID	EO-044D4F23AC
Generated	2026-08-05

Product Overview

Sensor/Actuator Cable, 5-Pole, M12 Straight Connector, A-Coding, M12 Straight Female A-Encoding, Cable Length: 3.2 m, Stainless Steel Knurling

Cable for sensors/actuators

Sensor/actuator cable, 5-position halogen-free, Plug straight M12, coding: A, on Socket straight M12, coding: A, cable length: 3.2 m, High-grade steel knurl

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Field Connectivity (IFC)
--------------	---

Additional Product Information

Technical dataProduct propertiesProduct type Sensor/actuator cable

Number of positions 5

No. of cable outlets 1

Shielded no

Coding A

Insulation characteristics

Overvoltage category II

Degree of pollution 3

Material specificationsFlammability rating according to UL 94 HB

Seal material NBR
Material of grip body TPU, hardly inflammable, self-extinguishing
Contact material CuSn
Contact surface material Ni/Au
Contact carrier material TPU GF
Material for screw connection Stainless steel
Electrical propertiesContact resistance $\leq 5 \text{ m}\Omega$
Insulation resistance $\geq 100 \text{ M}\Omega$
Nominal voltage UN 48 V AC
60 V DC
Nominal current IN 4 A
Mechanical propertiesMechanical data
Insertion/withdrawal cycles ≥ 100
SignalingStatus display No
Status display present No
ConnectorConnection 1
Type Plug straight M12
Number of positions 5
Coding type A
Connection 2
Type Socket straight M12
Number of positions 5
Coding type A
Cable/lineCable length 3.2 m
PUR halogen-free black [PUR]
Dimensional drawing
Shielded no
UL AWM Style 20549
Cable weight 33 kg/km
Cable type PUR halogen-free black
Cable type (abbreviation) PUR
External cable diameter 4.55 mm $\pm 0.15 \text{ mm}$
Outer sheath, material PUR
External sheath, color black-gray RAL 7021
Conductor material Bare Cu litz wires
Conductor structure signal line 42x 0.10 mm
AWG signal line 22
Conductor cross section 5x 0.34 mm² (Signal line)
Material wire insulation PP
Thickness, insulation approx. 0.5 mm
Wire diameter incl. insulation 1.27 mm 0.05 mm (Signal line)
Single wire, co...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-5P-M12MS/3,2-PUR/M12FS VA with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.