

INDUSTRIAL COMPONENT DATA

SAC-5P-M12MS/ 3,9-PUR/M12FR VA 1426339 PHOENIX CONTACT Cable for sensors/actuators

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-5P-M12MS/ 3,9-PUR/M12FR VA



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-5P-M12MS/ 3,9-PUR/M12FR VA
Catalog number	1426339
Category	Sensor-actuator patch cord
Minimum order	100 Pcs
Document ID	EO-3801F4FE2A
Generated	2026-08-05

Product Overview

Cable for sensors/actuators

Sensor/actuator cable, 5-position, PUR halogen-free, black-gray RAL 7021, Plug straight M12, coding: A, on Socket angled M12, coding: A, cable length: 3.9 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Industrial Field Connectivity (IFC)

Additional Product Information

Technical dataProduct propertiesProduct type Sensor/actuator cable

Number of positions 5

Application Standard

No. of cable outlets 1

Shielded no

Coding A

Insulation characteristics

Overvoltage category II

Degree of pollution 3

Material specificationsFlammability rating according to UL 94 HB

Seal material NBR

Material of grip body TPU, hardly inflammable, self-extinguishing

Contact material CuSn

Contact surface material Ni/Au
Contact carrier material TPU GF
Material for screw connection Stainless steel
Outer sheath, material PUR
Conductor material Bare Cu litz wires
Electrical propertiesContact resistance $\leq 5 \text{ m}\Omega$
Insulation resistance $\geq 100 \text{ M}\Omega$
Nominal voltage UN 48 V AC
60 V DC
Nominal current IN 4 A
Protective circuit unwired
Max. conductor resistance $58 \text{ m}\Omega/\text{m}$
Mechanical propertiesMechanical data
Insertion/withdrawal cycles ≥ 100
Max. bending cycles 4000000
SignalingStatus display No
Status display present No
ConnectorConnection 1
Type Plug straight M12
Number of positions 5
Coding type A
Number of positions 5
Connection 2
Type Socket angled M12
Number of positions 5
Coding type A
Number of positions 5
Cable/lineCable length 3.9 m
PUR halogen-free black [PUR]
Dimensional drawing
Cable weight 33 kg/km
UL AWM Style 20549
Number of positions 5
Shielded no
Cable type PUR halogen-free black [PUR]
Conductor structure signal line 42x 0.10 mm
AWG signal line 22
Conductor cross section 5x 0.34 mm² (Signal line)
Wire diameter incl. insulation 1.27 mm 0.05 mm (Signal line)
External cable....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-5P-M12MS/ 3,9-PUR/M12FR VA with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.