

## INDUSTRIAL COMPONENT DATA

# IPC 16/ 2-GF-10,16 GY 1705611 PHOENIX CONTACT Base housing, rated current: 76 A, number of poles: 2, pitch: ..

Brand: PHOENIX CONTACT | Manufacturer Part Number: IPC 16/ 2-GF-10,16 GY



|                 |                                 |
|-----------------|---------------------------------|
| Manufacturer    | PHOENIX CONTACT                 |
| MPN / Reference | IPC 16/ 2-GF-10,16 GY           |
| Catalog number  | 1705611                         |
| Category        | Printed circuit board connector |
| Minimum order   | 1 Pcs                           |
| Document ID     | EO-DA85A7FFD4                   |
| Generated       | 2026-08-05                      |

## Product Overview

IPC 16/ 2-GF-10,16 GY 1705611 PHOENIX CONTACT Base housing, rated current: 76 A, number of poles: 2, pitch: ..

## STRUCTURED PRODUCT DATA

## Technical Specifications

| TECHNICAL ATTRIBUTE                       | VALUE           |
|-------------------------------------------|-----------------|
| Connector model (EF007495)                | Fixed connector |
| Contact type (EF001587)                   | Bus             |
| Number of poles (EF001391)                | 2               |
| Number of plug-in contact rows (EF006935) | 1               |
| Modular spacing contacts (EF007326)       | 10.16 mm        |
| Modular spacing connections (EF006827)    | 10.16 mm        |
| Rated current In (EF008250)               | 76 A            |
| Rated voltage (EF000228)                  | 1000 V          |
| Rated surge voltage (EF002993)            | 8 kV            |
| Over voltage category (EF006785)          | III             |
| Pollution degree (EF006786)               | 2               |
| Material of contact surface (EF004020)    | Silver          |
| Type of electric connection (EF003961)    | Other           |
| Diameter connection pin (EF006823)        | 1.7 mm          |
| Length pin (EF006825)                     | 4 mm            |

**CONTINUED**

## Technical Specifications

| TECHNICAL ATTRIBUTE                                                      | VALUE            |
|--------------------------------------------------------------------------|------------------|
| Material insulation body (EF007543)                                      | Other            |
| Housing colour (EF000136)                                                | Grey             |
| Inflammability class of insulation material according to UL94 (EF002521) | V0               |
| Operating temperature (EF002393)                                         | -40 °C           |
| Type of fastening (EF002442)                                             | Other            |
| Type of banding (EF007011)                                               | Carton (for SMD) |

## Classification & Catalog Path

|              |                                        |
|--------------|----------------------------------------|
| eCl@ss 7.1   | 21043711                               |
| eCl@ss 8.0   | 21043711                               |
| eCl@ss 9.0   | 21043711                               |
| ETIM 5.0     | EC002246                               |
| ETIM 6.0     | EC002246                               |
| ETIM 7.0     | EC002246                               |
| Catalog path | PHOENIX CONTACT > PCB Connectors (PCC) |

## Additional Product Information

Base housing, rated current: 76 A, number of poles: 2, pitch: 10.16 mm, color: gray, contact surface: silver, mounting: Wave soldering

Printed circuit board base housing, nominal section: 16 mm<sup>2</sup>, color: gray, nominal current: 76 A, nominal voltage (III/2): 1000 V, contact surface: silver, contact type: Female, number of potentials: 2, number of rows: 1, number of poles: 2, number of connections: 2, family of articles: IPC 16/.. -GF, pitch: 10.16 mm, mounting: Wave welding, pin arrangement: Linear pin arrangement, pin length [P]: 4 mm, number of solder pins per potential: 3, plug-in system: COMBICON PC 16, Plug-in face orientation: Standard, locking: Screw lock, fixing type: Air clamping (thread), packaging type: boxed

### REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / IPC 16/ 2-GF-10,16 GY with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

#### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.