

INDUSTRIAL COMPONENT DATA

SAC-5P-M12MS/5,0-802/M12FS 1423574 PHOENIX CONTACT

Sensor/actuator cable SAC-5P-M12MS/5,0-802/M12FS 1423574

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-5P-M12MS/5,0-802/M12FS



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-5P-M12MS/5,0-802/M12FS
Catalog number	1423574
Category	Sensor-actuator patch cord
Minimum order	50 Pcs
Document ID	EO-0946174692
Generated	2026-08-04

Product Overview

Sensor/actuator cable - SAC-5P-M12MS/5,0-802/M12FS - 1423574

Sensor/actuator cable, 5-pole, halogen-free, solder-resistant, highly flexible, grey RAL 7001, M12 straight male connector, encoding: A, to M12 straight connection female, coding: A, cable length: 5 m, for robotics and drag chains

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > Industrial Field Connectivity (IFC)**

Additional Product Information

Sensor/actuator cable, 5-position, PUR halogen-free, resistant to welding sparks, highly flexible, gray RAL 7001, Plug straight M12, A-coded, on Socket straight M12, A-coded, cable length: 5 m, for robots and drag chains

Key Commercial Data

Orderkey 1423574

Packing unit 1

GTIN 4055626347127

Custom tariff number 85444290

Dimensions

Length of cable 5 m

General

Rated voltage 48 V AC

60 V DC

Number of positions 5

Cable

Note Due to the extremely robust outer sheath, this cable should only be stripped in 5 cm increments.

Cable type PUR, halogen-free, highly stranded, resistant to welding sparks, gray

Cable type (abbreviation) 802

Cable abbreviation Li12Y11Y-HF

Conductor cross section 5x 0.34 mm² (Signal line)

AWG signal line 22

Conductor structure signal line 42x 0.10 mm

Core diameter including insulation 1.3 mm ±0.05 mm (Signal line)

Wire colors Black, brown, blue, white, green/yellow

Overall twist 5 wires around filler to the core

External sheath, color gray RAL 7001

External cable diameter D 5.1 mm ±0.2 mm

Minimum bending radius, fixed installation 5 x D

Minimum bending radius, flexible installation 5 x D

Number of bending cycles 10000000

Minimum bending radius, drag chain applications 7,5 x D

Traversing path 5 m

Traversing rate 3.3 m/s

Acceleration 5 m/s²

Number of bending cycles 15000000

Bending radius 50 mm

Traversing path 0.9 m

Traversing rate 5 m/s

Acceleration 30 m/s²

Torsion force ± 360 °/m (1 000 000 torsion cycles)

Outer sheath, material PUR

Material conductor insulati...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-5P-M12MS/5,0-802/M12FS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.