

INDUSTRIAL COMPONENT DATA

SAC-5P-M12MS/ 5,0-PUR/M12FS SH 1693092 PHOENIX CONTACT Sensor/actuator cable

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-5P-M12MS/ 5,0-PUR/M12FS SH



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-5P-M12MS/ 5,0-PUR/M12FS SH
Catalog number	1693092
Category	Sensor-actuator patch cord
Minimum order	10 Pcs
Document ID	EO-8DFE834A03
Generated	2026-08-06

Product Overview

Sensor/actuator cable

Sensor/actuator cable, 5-pole, halogen-free PUR, greyish black RAL 7021, shielded, M12 straight male connector, coding: A, to M12 straight connection female, coding: A, cable length: 5 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Industrial Field Connectivity (IFC)

Additional Product Information

Key Commercial Data

Orderkey 1693092

Packing unit 5 pc

Minimum order quantity 50 pc

Note Made to Order (non-returnable)

GTIN 4017918426125

Weight per Piece (excluding packing) 257.700 g

Custom tariff number 85444290

Country of origin PL (Poland)

Dimensions

Length of cable 5 m

Ambient conditions

Degree of protection IP67

General

Rated current at 40°C 4 A

Rated voltage 48 V AC

60 V DC

Number of positions 5

Coding A - standard

Status display No

Insertion/withdrawal cycles ≥ 100 **Material**

Contact material CuSn

Contact surface material Ni/Au

Cable

Cable type PUR halogen-free black

Cable type (abbreviation) PUR

Cable abbreviation LiF9YC11Y

UL AWM style 20549

Conductor cross section 5x 0.34 mm² (Signal line)

AWG signal line 22

Conductor structure signal line 42x 0.10 mm

Core diameter including insulation 1.27 mm ± 0.02 mm (Signal line)Thickness, insulation ≥ 0.21 mm

Wire colors Brown, white, blue, black, gray

Overall twist 5 wires around filler to the core

Shielding Tinned copper braided shield

Optical shield covering 85 %

External sheath, color black-gray RAL 7021

External cable diameter D 5.9 mm ± 0.2 mm

Smallest bending radius, fixed installation 29.5 mm

Smallest bending radius, movable installation 59 mm (up to +60°C)

Number of bending cycles 4000000

Bending radius 59 mm

Traversing path 10 m

Traversing rate 3 m/s

Acceleration 10 m/s²

Cable weight 48 kg/km

Outer sheath, material PUR

Material conductor insulation PP

Conductor material Bare Cu litz wires

Insulation resistance 70 G?^{*}...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-5P-M12MS/ 5,0-PUR/M12FS SH with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.