

INDUSTRIAL COMPONENT DATA

SAC-5P-M12MS/ 5,0-PVC SH 1426507 PHOENIX CONTACT

Cable for sensors/actuators 5-pin, PVC, black RAL 9005, shi..

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-5P-M12MS/ 5,0-PVC SH



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-5P-M12MS/ 5,0-PVC SH
Catalog number	1426507
Category	Sensor-actuator patch cord
Minimum order	50 Pcs
Document ID	EO-5173AF137A
Generated	2026-08-06

Product Overview

Cable for sensors/actuators 5-pin, PVC, black RAL 9005, shielded, Plug straight M12, coded A, end of free cable, cable length: 5 m

Sensor/actuator cable, 5-pole, PVC, black RAL 9005, shielded, M12 straight male connector, coding: A, to free cable end, cable length: 5 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Field Connectivity (IFC)
--------------	---

Additional Product Information

Cable for sensors/actuators 5-pin, PVC, black RAL 9005, shielded, Plug straight M12, coded A, end of free cable, cable length: 5 m

Data commercial

Key order One million four hundred twenty six thousand five hundred seven

Packing unit 1 pcs

Key selling BF1CKA -

Minimum order quantity 50 pcs

EAN Four trillion fifty five billion six hundred twenty six million four hundred sixty two thousand two hundred nineteen

Unit weight (excluding packaging) 302,500 g

Tariff number tariff Eighty five million four hundred seventy two thousand

Measures

Cable length 5 m

Environmental conditions

Room temperature (service) -25 °C ... 90 °C (male / female)

Overview

Current sizing at 40 °C 4 To

Tension sizing 48 V AC

60 V DC

Number of poles Five

Insulation resistance $\geq 100 \text{ M}\Omega$

Encoding A - standard

Standards/specifications Plug-in connector M12 to IEC 61076-2-101

Status indication Not

Protective circuit/component protection without connect

Category surge II

Pollution degree Three

Cycles of plug ≥ 100

Material

Class of flammability according to UL 94 HB

Material contact CuSn

Material contact surface Ni/Au

Material support of contacts TPU GF

Material body grip TPU fire-retardant, self-extinguishing

Material knurled Die-cast zinc, nickel plated

Material of the board NBR

Standards and specifications

Name of standard Plug-in connector M12

Standards/specifications IEC 61076-2-101

Class of flammability according to UL 94 HB

Cable

Type of cable Black PVC

Cable type (abbreviation) PVC

Section of driver 5x 0,...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-5P-M12MS/ 5,0-PVC SH with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.