

INDUSTRIAL COMPONENT DATA

SAC-5P-M12MS/ 7,1-PUR/M12FS VA 1426378 PHOENIX CONTACT Sensor/actuator cable SAC-5P-M12MS/ 7,1-PUR/M12FS VA ..

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-5P-M12MS/ 7,1-PUR/M12FS VA



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-5P-M12MS/ 7,1-PUR/M12FS VA
Catalog number	1426378
Category	Sensor-actuator patch cord
Minimum order	100 Pcs
Document ID	EO-24AE986685
Generated	2026-08-06

Product Overview

Sensor/actuator cable - SAC-5P-M12MS/ 7,1-PUR/M12FS VA - 1426378

Sensor/actuator cable, 5-pole, halogen-free PUR, greyish black RAL 7021, Straight connector M12, coding: A, to Straight female M12, coding: A, cable length: 7.1 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Industrial Field Connectivity (IFC)

Additional Product Information

Sensor/actuator cable, 5-position, PUR halogen-free, black-gray RAL 7021, Plug straight M12, A-coded, cable length: 7.1 m

Key Commercial Data

Orderkey 1426378

Packing unit 1

GTIN 4055626459080

Custom tariff number 85444290

Dimensions

Length of cable 7.1 m

General

Rated current at 40°C 4 A

Rated voltage 48 V AC

60 V DC
Number of positions 5
Insulation resistance $\geq 100 \text{ M}\Omega$
Coding A - standard
Status display No
Overvoltage category II
Degree of pollution 3
Insertion/withdrawal cycles ≥ 100
Material
Flammability rating according to UL 94 HB
Contact material CuSn
Contact surface material Ni/Au
Contact carrier material TPU GF
Material of grip body TPU, hardly inflammable, self-extinguishing
Material, knurls Stainless steel
Sealing material NBR
Standards and Regulations
Flammability rating according to UL 94 HB
Cable
Cable type PUR halogen-free black
Cable type (abbreviation) PUR
Cable abbreviation Li9Y11Y
UL AWM style 20549 / 10493 (80°C/300 V)
Conductor cross section $5 \times 0.34 \text{ mm}^2$ (Signal line)
AWG signal line 22
Conductor structure signal line $42 \times 0.10 \text{ mm}$
Core diameter including insulation $1.27 \text{ mm} \pm 0.02 \text{ mm}$ (Signal line)
Thickness, insulation $\geq 0.21 \text{ mm}$
Wire colors brown, white, blue, black, green-yellow
Overall twist 5 wires around filler to the core
External sheath, color black-gray RAL 7021
Outer sheath thickness approx. 0.7 mm
External cable diameter $D 5 \text{ mm} \pm 0.15 \text{ mm}$
Smallest bending radius, fixed installation 25 mm
Smallest bending radius, movable installation 50 mm
Number of ben...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-5P-M12MS/ 7,1-PUR/M12FS VA with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.