

INDUSTRIAL COMPONENT DATA

SAC-5P-M12MSB/0,8-PUR SH 1075085 PHOENIX CONTACT

Sensor/actuator cable, 5-position, PUR halogen-free, black-..

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-5P-M12MSB/0,8-PUR SH



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-5P-M12MSB/0,8-PUR SH
Catalog number	1075085
Category	Sensor-actuator patch cord
Minimum order	100 Pcs
Document ID	EO-129E05A516
Generated	2026-08-06

Product Overview

Sensor/actuator cable, 5-position, PUR halogen-free, black-gray RAL 7021, shielded, Plug straight M12, B-coded, on free cable end, cable length: 0.8 m

Sensor/actuator cable, 5-pole, halogen-free PUR, greyish black RAL 7021, shielded, M12 straight male connector, coding: B, to free cable end, cable length: 0.8 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Industrial Field Connectivity (IFC)

Additional Product Information

Key Commercial Data

Orderkey 1075085

Packing unit 1

GTIN 4055626779010

Custom tariff number 85444290

Drawings

General

Classifications

Dimensions

Cable

Drawings

Cable cross section

PUR halogen-free black [PUR]

[Back to top](#)Dimensions

Length of cable 0.8 m

[Back to top](#)General

Number of positions 5

[Back to top](#)Cable

Cable type PUR halogen-free black

Cable type (abbreviation) PUR

Cable abbreviation LiF9YC11Y

UL AWM style 20549

Conductor cross section 5x 0.34 mm² (Signal line)

AWG signal line 22

Conductor structure signal line 42x 0.10 mm

Core diameter including insulation 1.27 mm ±0.02 mm (Signal line)

Thickness, insulation ≥ 0.21 mm

Wire colors Brown, white, blue, black, gray

Overall twist 5 wires around filler to the core

Shielding Tinned copper braided shield

Optical shield covering 85 %

External sheath, color black-gray RAL 7021

External cable diameter D 5.9 mm ±0.2 mm

Smallest bending radius, fixed installation 29.5 mm

Smallest bending radius, movable installation 59 mm (up to +60°C)

Number of bending cycles 4000000

Bending radius 59 mm

Traversing path 10 m

Traversing rate 3 m/s

Acceleration 10 m/s²

Cable weight 48 kg/km

Outer sheath, material PUR

Material conductor insulation PP

Conductor material Bare Cu litz wires

Insulation resistance 70 G?·km (at 20 °C)

Conductor resistance max. 57 ?/km (at 20 °C)

Nominal voltage, cable 300 V (at 20 °C)

Test voltage Core/Core 3000 V (at 20 °C)

Special properties Flexible cable conduit capable

Flame resistance in acc. with UL FT-2

Halogen-f...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-5P-M12MSB/0,8-PUR SH with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.