

INDUSTRIAL COMPONENT DATA

SAC-5P-M12MSB/1,0-PUR/M12FRB 1423761 PHOENIX CONTACT Sensor/actuator cable

SAC-5P-M12MSB/1,0-PUR/M12FRB 1423..

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-5P-M12MSB/1,0-PUR/M12FRB



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-5P-M12MSB/1,0-PUR/M12FRB
Catalog number	1423761
Category	Sensor-actuator patch cord
Minimum order	50 Pcs
Document ID	EO-D2545F3DC0
Generated	2026-08-06

Product Overview

Sensor/actuator cable - SAC-5P-M12MSB/1,0-PUR/M12FRB - 1423761

Sensor/actuator cable, 5-pole, halogen-free PUR, greyish black RAL 7021, Straight male connector M12, coding: B, a Angled connection female M12, coding: B, cable length: 1 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > Industrial Field Connectivity (IFC)**

Additional Product Information

Sensor/actuator cable, 5-position, PUR halogen-free, black-gray RAL 7021, Plug straight M12, B-coded, on Socket angled M12, B-coded, cable length: 1 m

Key Commercial Data

Orderkey 1423761

Packing unit 1

GTIN 4055626352558

Custom tariff number 85444290

Dimensions

Length of cable 1 m

Stripping length of the free conductor end 50 mm

Ambient conditions

Ambient temperature (operation) -25 °C ... 90 °C (Plug / socket)

General

Rated current at 40°C 4 A

Rated voltage 48 V AC

60 V DC

Number of positions 5

Insulation resistance $\geq 100 \text{ M}\Omega$

Coding B - inverse

Status display No

Overvoltage category II

Degree of pollution 3

Insertion/withdrawal cycles ≥ 100

Material

Flammability rating according to UL 94 HB

Contact material CuSn

Contact surface material Ni/Au

Contact carrier material TPU GF

Material of grip body TPU, hardly inflammable, self-extinguishing

Material, knurls Zinc die-cast, nickel-plated

Sealing material NBR

Standards and Regulations

Flammability rating according to UL 94 HB

Cable

Cable type PUR halogen-free black

Cable type (abbreviation) PUR

Cable abbreviation Li9Y11Y

UL AWM style 20549 / 10493 (80°C/300 V)

Conductor cross section $5 \times 0.34 \text{ mm}^2$ (Signal line)

AWG signal line 22

Conductor structure signal line $42 \times 0.10 \text{ mm}$

Core diameter including insulation $1.27 \text{ mm} \pm 0.02 \text{ mm}$ (Signal line)

Thickness, insulation $\geq 0.21 \text{ mm}$

Wire colors brown, white, blue, black, green-yellow

Overall twist 5 wires around filler to the core

External sheath, color black-gray RAL 7021

Outer sheath thicknes...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-5P-M12MSB/1,0-PUR/M12FRB with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.