

INDUSTRIAL COMPONENT DATA

SAC-5P-M12MSL/10,0-290/FSL FE 1276418 PHOENIX CONTACT Power cable, 5-pole, halogen-free PUR, grey RAL 7001, ..

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-5P-M12MSL/10,0-290/FSL FE



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-5P-M12MSL/10,0-290/FSL FE
Catalog number	1276418
Category	Sensor-actuator patch cord
Minimum order	1 Pcs
Document ID	EO-1B88F5C55F
Generated	2026-08-06

Product Overview

Power cable, 5-pole, halogen-free PUR, grey RAL 7001, Straight connector M12, coding: L, to Straight female M12, coding:

L, cable length: 10 m, for direct current up to 12 A/63 V

Power cable, 5-pole, halogen-free PUR, grey RAL 7001, cable length: 10 m, for direct current up to 12 A/63 V

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Industrial Field Connectivity (IFC)

Additional Product Information

ETIM for 1276418 Sensors (EC001855)

Feature Name

Feature Value

Number of poles (EF001391)

5

Type of electrical connection, field-sided (EF005525)

M12

Type of plug-in contact, field sided (EF006269)

Male (plug)

Positioning cable feed, field-sided (EF005928)

Straight

Type of electrical connection, box-sided (EF005524)
M12
Type of plug-in contact, box-sided (EF008386)
Female (bus)
Positioning cable feed, box-sided (EF005927)
Straight
Cable length (EF000536)
10 m
Material of cable sheath (EF004136)
Other
Halogen free (EF000025)
Yes
Colour cable sheath (EF008249)
Other
With LED indication (EF005950)
No
Screened (EF000881)
No
Vulcanize (EF004115)
No
Material contact body (EF008248)
Other
Permitted cable outer temperature after assembling without vibration (EF001686)
-50 °C
Permitted cable outer temperature during assembling/handling (EF001685)
-30 °C
Rated voltage (EF000228)
63 V
Degree of protection (IP) (EF005474)
IP65

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-5P-M12MSL/10,0-290/FSL FE with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.