

INDUSTRIAL COMPONENT DATA

SAC-5P-M12YF/M12FS-M12MS VP 1526253 PHOENIX CONTACT Y distributor

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-5P-M12YF/M12FS-M12MS VP



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-5P-M12YF/M12FS-M12MS VP
Catalog number	1526253
Category	Sensor actuator adapter
Minimum order	5 Pcs
Document ID	EO-789EEDF894
Generated	2026-08-05

Product Overview

Y distributor

Y-splitter, 5-pole, Straight female M12, coding: A, a Straight female M12, coding: A and Straight connector M12, coding: A, parallel purge nozzle

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > Industrial Field Connectivity (IFC)**

Additional Product Information

Key Commercial Data

Orderkey 1526253

Packing unit 5 pc

Minimum order quantity 5 pc

Note Made to Order (non-returnable)

GTIN 4017918954291

Weight per Piece (excluding packing) 26.250 g

Custom tariff number 85366990

Country of origin PL (Poland)

Dimensions

Center distance 18 mm

Ambient conditions

Degree of protection IP65

IP67

General

Rated current at 40°C 4 A

Rated voltage 48 V AC

60 V DC

Number of positions 5

Insulation resistance $\geq 100 \text{ M}\Omega$

Coding A - standard

Standards/regulations M12 connector IEC 61076-2-101

Status display No

Overvoltage category II

Degree of pollution 3

Insertion/withdrawal cycles ≥ 100

Torque 0.4 Nm (M12 connector)

Material

Flammability rating according to UL 94 HB

Contact material CuZn

Contact surface material Ni/Au

Contact carrier material TPU GF

Material of grip body TPU, hardly inflammable, self-extinguishing

Material, knurls Zinc die-cast, nickel-plated

Sealing material NBR

Standards and Regulations

Standard designation M12 connector

Standards/regulations IEC 61076-2-101

Flammability rating according to UL 94 HB

Classifications

eCl@ss 4.027060306eCl@ss 4.127060306eCl@ss 5.027061801eCl@ss 5.127061800eCl@ss 6.027279200eCl@ss
7.027440104eCl@ss 8.027440104eCl@ss 9.027440106

ETIM 2.0EC000830ETIM 3.0EC001855ETIM 4.0EC001855ETIM 5.0EC002062ETIM 6.0EC002925

UNSPSC 6.0131251501UNSPSC 7.090131251501UNSPSC 1131251501UNSPSC 12.0131251501UNSPSC
13.231251501

ETIM for 1526253 Sensors (EC002925)

Feature Name

Feature Value

Model (EF000010)

Y-adapter

Screened (EF0008...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-5P-M12YF/M12FS-M12MS VP with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.