

INDUSTRIAL COMPONENT DATA

UCS HH 237-195 9005 2203357 PHOENIX CONTACT Housing half shell

Brand: PHOENIX CONTACT | Manufacturer Part Number: UCS HH 237-195 9005



Manufacturer	PHOENIX CONTACT
MPN / Reference	UCS HH 237-195 9005
Catalog number	2203357
Category	Extruded profile modular housing
Minimum order	10 Pcs
Document ID	EO-2587B5DFEA
Generated	2026-08-05

Product Overview

Housing half shell

Housing half-frame for mounting a UCS housing with the dimensions 237 x 195 mm; polycarbonate material; black color similar to RAL 9005

Housing half shell for creating a UCS housing of 237 x 195 mm; material: polycarbonate; color: black similar to RAL 9005

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Housing (HS)
--------------	--------------------------------

Additional Product Information

Technical dataNotesAssembly note Refer to the data sheet for the range in the download area.

Product propertiesProduct type Housing half shells

Housing type Universal housings

Housing series UCS

Product family UCS 237-195

Type Housing half shell

Ventilation openings present no

Data management status

Article revision 00

DimensionsDimensional drawing

Width 237 mm

Height 195 mm

Depth 21.75 mm
PCB design
PCB thickness 0.8 mm ... 3 mm
Material specificationsColor (Housing) black (RAL 9005)
Flammability rating according to UL 94 V0
CTI according to IEC 60112 225
Insulating material PC
Housing material PC
Surface characteristics untreated
Environmental and real-life conditionsVibration test
Specification IEC 60068-2-6:2007-12
Frequency 10 - 150 - 10 Hz
Sweep speed 1 octave/min
Amplitude 0.15 mm (10 Hz ... 58.1 Hz)
Acceleration 2g (58.1 Hz ... 150 Hz)
Test duration per axis 2.5 h
Test directions X-, Y- and Z-axis
Glow-wire test
Specification IEC 60695-2-11:2014-02
Temperature 850 °C
Time of exposure 30 s
Thermal stability / ball thrust test
Specification IEC 60695-10-2:2014-02
Temperature 125 °C
Test duration 1 h
Force 20 N
Mechanical strength / tumbling barrel
Specification IEC 60068-2-31:2008-05
Height of fall 50 cm
Frequency 50
Shocks
Specification IEC 60068-2-27:2008-02
Pulse shape Half-sine
Acceleration 15g
Shock duration 11 ms
Number of shocks per direction 3
Test directions X-, Y- and Z-axis (pos. and neg.)
Test for substances that would hinder coating with paint or varnish
S...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UCS HH 237-195 9005 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.