

INDUSTRIAL COMPONENT DATA

SAC-5P-MR/ 0,2-923/FR CAN SCO 1416172 PHOENIX CONTACT Bus system cable SAC-5P-MR/ 0,2-923/FR CAN SCO 1416172

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-5P-MR/ 0,2-923/FR CAN SCO



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-5P-MR/ 0,2-923/FR CAN SCO
Catalog number	1416172
Category	Sensor-actuator patch cord
Minimum order	50 Pcs
Document ID	EO-12E6258364
Generated	2026-08-05

Product Overview

Bus system cable - SAC-5P-MR/ 0,2-923/FR CAN SCO - 1416172

Bus system cable, CANopen®, DeviceNet™, 5-pole halogen-free, shielded, M12 angled connector, coding: A SPEEDCON, to M12 angled female, coding: A SPEEDCON, cable length: 0.2 m, Unshielded plug-in connector

Bus system cable, CANopen®, DeviceNet™, 5-position, PUR halogen-free, silver-grey RAL 7001, shielded, Plug angled M12 SPEEDCON, coding: A, on Socket angled M12 SPEEDCON, coding: A, cable length: 0.2 m, Connector unshielded

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Field Connectivity (IFC)
--------------	---

Additional Product Information

Technical dataProduct propertiesProduct type Data cable preassembled

Application Bus system

Sensor type CANopen®

Number of positions 5

No. of cable outlets 1

Shielded yes

Coding A

Data management status

Article revision 01

Insulation characteristics
Overvoltage category II
Degree of pollution 3
InterfacesBus system CANopen®/DeviceNet™
Signal type/category CANopen®
DeviceNet™
SignalingStatus display no
Status display present No
Electrical propertiesNominal voltage UN 48 V AC
60 V DC
Nominal current IN 4 A
Transmission medium Copper
Material specificationsFlammability rating according to UL 94 HB
Seal material NBR
Material of grip body TPU, hardly inflammable, self-extinguishing
Contact material CuSn
Contact surface material Ni/Au
Contact carrier material TPU GF
Material for screw connection Zinc die-cast, nickel-plated
ConnectorConnection 1
Type Plug angled M12 SPEEDCON
Number of positions 5
Locking type SPEEDCON
Coding type A (Standard)
Connection 2
Type Socket angled M12 SPEEDCON
Number of positions 5
Locking type SPEEDCON
Coding type A (Standard)
Cable/lineCable length 0.2 m
CANopen®/DeviceNet™, PUR, gray [923]
Dimensional drawing
Cable weight 90 kg/km
UL AWM Style 21198 (80°C/300 V)
Number of positions 4
Shielded yes
Cable type CANopen®/DeviceNet™, PUR, gray [923]
Conductor structure 2xAWG24/19+2xAWG22/19
Conductor structure signal line 19x 0.13 mm
AWG signal line 24
Conductor cross section 2x 0.25 mm² (Data cable)
2x 0.34 mm² (Power supply)
1x 0.34 mm² (Drain wire)
Wire....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-5P-MR/ 0,2-923/FR CAN SCO with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.