

INDUSTRIAL COMPONENT DATA

SAC-5P-M12MR/ 1,1-PUR/M12FR SH 1045558 PHOENIX CONTACT Cable for sensors/actuators, 5-pole, PUR halogen-free..

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-5P-MR/ 1,1-PUR/FR SH SCO



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-5P-MR/ 1,1-PUR/FR SH SCO
Catalog number	1045558
Category	Sensor-actuator patch cord
Minimum order	25 Pcs
Document ID	EO-C021D9BDF2
Generated	2026-08-05

Product Overview

Cable for sensors/actuators, 5-pole, PUR halogen-free, black-gray RAL 7021, Plug angled M12 SPEEDCON, coded, to the connection socket angled M12 SPEEDCON, coded, cable length: 1.1 m

Sensor/actuator cable, 5-pole, halogen-free PUR, greyish black RAL 7021, shielded, M12 SPEEDCON angled male connector, coding: A, to M12 SPEEDCON angled connection female, coding: A, cable length: 1.1 m

Sensor/actuator cable, 5-position, PUR halogen-free, black-gray RAL 7021, shielded (Advanced Shielding Technology), Plug angled M12 SPEEDCON, coding: A, on Socket angled M12 SPEEDCON, coding: A, cable length: 1.1 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Industrial Field Connectivity (IFC)

Additional Product Information

Technical dataProduct propertiesProduct type Sensor/actuator cable

Number of positions 5

Shielded yes

ConnectorConnection 1

Type Plug angled M12 SPEEDCON

Number of positions 5

Locking type SPEEDCON

Coding type A

Connection 2

Type Socket angled M12 SPEEDCON

Number of positions 5

Locking type SPEEDCON

Coding type A

Cable/lineCable length 1.1 m

PUR halogen-free black [PUR]

Dimensional drawing

Cable weight 43 kg/km

UL AWM Style 20549 / 10493 (80°C/300 V)

Number of positions 5

Shielded yes

Cable type PUR halogen-free black [PUR]

Conductor structure signal line 42x 0.10 mm

AWG signal line 22

Conductor cross section 5x 0.34 mm² (Signal line)

Wire diameter incl. insulation 1.27 mm ±0.02 mm (Signal line)

External cable diameter 5.25 mm ±0.2 mm

Outer sheath, material PUR

External sheath, color black-gray RAL 7021

Conductor material Bare Cu litz wires

Material wire insulation PP

Single wire, color brown, white, blue, black, gray

Thickness, insulation ≥ 0.21 mm

Thickness, outer sheath approx. 0.50 mm

Overall twist 5 wires around filler to the core

Optical shield covering 80 %

Max. conductor resistance max. 57 Ω/km (at 20 °C)

Insulation resistance 70 GΩ*km (at 20 °C)

Nominal voltage, cable 300 V (at 20 °C)

Test voltage Core/Core 3000 V (at 20 °C)

Smallest bending radius, fixed installation 26 mm

Smallest bending radius, movable installation 52 mm (up to +60 °C)

Dynamic load capacity (bending) Max. bending cycles: 10000000, Bending radius: 52 mm, Traversing path: 10 m,

Traversing rate: 3....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-5P-MR/ 1,1-PUR/FR SH SCO with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.