

INDUSTRIAL COMPONENT DATA

SAC-5P-MR/ 3,45-PUR/FS SCO 1417369 PHOENIX CONTACT

Sensor/actuator cable SAC-5P-MR/ 3,45-PUR/FS SCO 1417369

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-5P-MR/ 3,45-PUR/FS SCO



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-5P-MR/ 3,45-PUR/FS SCO
Catalog number	1417369
Category	Sensor-actuator patch cord
Minimum order	50 Pcs
Document ID	EO-54ADF003B2
Generated	2026-08-06

Product Overview

Sensor/actuator cable - SAC-5P-MR/ 3,45-PUR/FS SCO - 1417369

Sensor/actuator cable, 5 poles, halogen-free PUR, grey black RAL 7021, M12 angled connector, A-coded, in straight M12 female connector, A-coated, cable length: 3.45 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Field Connectivity (IFC)
--------------	---

Additional Product Information

Sensor/actuator cable, 5-pos., PUR, halogen-free, RAL 7021 (black gray), angled M12 connector (A-coded) to straight M12 socket (A-coded), cable length: 3.45 m

Key Commercial Data

Orderkey 1417369

Packing unit 1

GTIN 4055626090450

Custom tariff number 85444290

General

Rated voltage 48 V AC

60 V DC

Cable

Cable type PUR halogen-free black

Cable type (abbreviation) PUR

UL AWM style 20549
Conductor cross section 5x 0.34 mm² (Signal line)
AWG signal line 22
Conductor structure signal line 42x 0.10 mm
Core diameter including insulation 1.27 mm ±0.02 mm (Signal line)
Thickness, insulation approx. 0.5 mm
Wire colors brown, white, blue, black, green-yellow
External sheath, color black-gray RAL 7021
External cable diameter D 4.55 mm ±0.15 mm
Smallest bending radius, fixed installation 23 mm
Smallest bending radius, movable installation 46 mm
Number of bending cycles 10000000
Bending radius 50 mm
Traversing path 10 m
Traversing rate 3 m/s
Acceleration 10 m/s²
Cable weight 33 kg/km
Outer sheath, material PUR
Material conductor insulation PP
Conductor material Bare Cu litz wires
Insulation resistance $\geq 16 \text{ G}\cdot\text{km}$ (at 20 °C)
Conductor resistance max. 58 Ω/km (at 20 °C)
Nominal voltage, cable 300 V
Test voltage, cable 3000 V
Special properties Flexible cable conduit capable
Silicone-free
Free of substances which would hinder coating with paint or varnish
flexible
Flame resistance in accordance with UL 758/1581 FT2
DIN EN 60332-2-2 (20 s)
Halogen-free in accordance with DIN VDE 0472 part 815
R...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-5P-MR/ 3,45-PUR/FS SCO with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.