

INDUSTRIAL COMPONENT DATA

SAC-5P-MRC2/17-920/MRC3 SH 1NC 1163511 PHOENIX CONTACT Bus system cable, CANopen®, DeviceNet™, 5-pole, halog..

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-5P-MRC2/17-920/MRC3 SH 1NC



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-5P-MRC2/17-920/MRC3 SH 1NC
Catalog number	1163511
Category	Sensor-actuator patch cord
Minimum order	1 Pcs
Document ID	EO-90F28DC2E0
Generated	2026-08-05

Product Overview

Bus system cable, CANopen®, DeviceNet™, 5-pole, halogen-free PUR, lilac red RAL 4001, shielded, M12 SPEEDCON angled connector, coding: A, a M12 SPEEDCON angled connector, coding: A, cable length: 17 m, C2 and C3 output direction

Bus System Cable, CANopen®, DeviceNet™, 5-pole, halogen-free PUR, RAL 4001 violet, shielded, Male bent connector M12 SPEEDCON, encoding: A, a Male bent connector M12 SPEEDCON, encoding: A, cable length: 17 m, Output direction C2 and C3

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Industrial Field Connectivity (IFC)

Additional Product Information

ETIM for 1163511 Sensors (EC001855)

Feature Name

Feature Value

Number of poles (EF001391)

5

Type of electrical connection, field-sided (EF005525)

M12

Type of plug-in contact, field sided (EF006269)

Male (plug)
Positioning cable feed, field-sided (EF005928)
Angled
Type of electrical connection, box-sided (EF005524)
M12
Type of plug-in contact, box-sided (EF008386)
Male (plug)
Positioning cable feed, box-sided (EF005927)
Angled
Cable length (EF000536)
17 m
Material of cable sheath (EF004136)
Other
Halogen free (EF000025)
Yes
Colour cable sheath (EF008249)
Other
With LED indication (EF005950)
No
Screened (EF000881)
No
Vulcanize (EF004115)
No
Material contact body (EF008248)
Other
Material of contact surface (EF004020)
Other
Permitted cable outer temperature after assembling without vibration (EF001686)
-40 °C
Permitted cable outer temperature during assembling/handling (EF001685)
-30 °C
Rated current I_n (EF008250)
4 A
Rated voltage (EF000228)
48 V
Degree of protection (IP) (EF005474)
IP65

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-5P-MRC2/17-920/MRC3 SH 1NC with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.