

INDUSTRIAL COMPONENT DATA

SAC-5P-MS/0,25-28R SCO RAIL 1559180 PHOENIX CONTACT

Sensor/actuator cable, 5-pole, M12 SPEEDCON straight con..

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-5P-MS/0,25-28R SCO RAIL



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-5P-MS/0,25-28R SCO RAIL
Catalog number	1559180
Category	Sensor-actuator patch cord
Minimum order	100 Pcs
Document ID	EO-AA56147CF5
Generated	2026-08-03

Product Overview

Sensor/actuator cable, 5-pole, M12 SPEEDCON straight connector, coding: A, to free cable end, cable length: 0.25 m, For railway applications

Cable for sensors/actuators

Sensor/actuator cable, 5-position, Plug straight M12 SPEEDCON, coding: A, connected with unwired, on free cable end, cable length: 0.25 m, For railway applications

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Industrial Field Connectivity (IFC)

Additional Product Information

Technical dataNotesGeneral Further products with variable cable type and variable cable length can be found in the accessories section

Product propertiesProduct type Sensor/actuator cable

Number of positions 5

Application Railway applications

No. of cable outlets 1

Shielded yes

Coding A

Insulation characteristics

Overvoltage category II

Degree of pollution 3

Material specifications Flammability rating according to UL 94 V0

Material of grip body PA 6.6

Contact material CuSn

Contact surface material Ni/Au

Contact carrier material PA 6.6

Material for screw connection Zinc die-cast, nickel-plated

Electrical properties Contact resistance $\leq 5 \text{ m}\Omega$

Insulation resistance $\geq 100 \text{ M}\Omega$

Nominal voltage UN 48 V AC

60 V DC

Nominal current IN 4 A

Protective circuit unwired

Mechanical properties Mechanical data

Insertion/withdrawal cycles ≥ 100

Signaling Status display No

Status display present No

Connector Connection 1

Type Plug straight M12 SPEEDCON

Number of positions 5

Locking type SPEEDCON

Coding type A

Connection 2

Type free cable end

Cable/line Cable length 0.25 m

Shielded black RADOX®[28R]

Dimensional drawing

Shielded yes

Cable weight 70 kg/km

Cable type Shielded black RADOX®

Cable type (abbreviation) 28R

External cable diameter 6.2 mm $\pm 0.3 \text{ mm}$

Outer sheath, material PE-X

External sheath, color black

Conductor material Tin-plated Cu litz wires

Conductor structure signal line 19x 0.18 mm

AWG signal line 20

Conductor cross section 5x 0.5 mm²

Material wire insulation PE-X

Wire diameter incl. insul...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-5P-MS/0,25-28R SCO RAIL with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.