

INDUSTRIAL COMPONENT DATA

SAC-5P-MS/11,5-920/FRC3 SH 1NC 1163932 PHOENIX CONTACT Bus system cable, CANopen®, DeviceNet™, 5-pole, halog..

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-5P-MS/11,5-920/FRC3 SH 1NC



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-5P-MS/11,5-920/FRC3 SH 1NC
Catalog number	1163932
Category	Sensor-actuator patch cord
Minimum order	50 Pcs
Document ID	EO-7C8849128C
Generated	2026-08-04

Product Overview

Bus system cable, CANopen®, DeviceNet™, 5-pole, halogen-free PUR, lilac red RAL 4001, shielded, Straight M12 SPEEDCON connector, coding: A, a Bent female M12 SPEEDCON, coding: A, cable length: 11.5 m, Output direction C3
 Bus System Cable, CANopen®, DeviceNet™, 5-pole, halogen-free PUR, RAL 4001 violet, shielded, M12 SPEEDCON straight male connector, encoding: A, a Female bent connection M12 SPEEDCON, encoding: A, cable length: 11.5 m, Output direction C3

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Industrial Field Connectivity (IFC)

Additional Product Information

ETIM for 1163932 Sensors (EC001855)

Feature Name

Feature Value

Number of poles (EF001391)

5

Type of electrical connection, field-sided (EF005525)

M12

Type of plug-in contact, field sided (EF006269)

Female (bus)

Positioning cable feed, field-sided (EF005928)
Angled
Type of electrical connection, box-sided (EF005524)
M12
Type of plug-in contact, box-sided (EF008386)
Male (plug)
Positioning cable feed, box-sided (EF005927)
Straight
Cable length (EF000536)
11.5 m
Material of cable sheath (EF004136)
Other
Halogen free (EF000025)
Yes
Colour cable sheath (EF008249)
Other
With LED indication (EF005950)
No
Screened (EF000881)
No
Vulcanize (EF004115)
No
Material contact body (EF008248)
Other
Material of contact surface (EF004020)
Other
Permitted cable outer temperature after assembling without vibration (EF001686)
-40 °C
Permitted cable outer temperature during assembling/handling (EF001685)
-30 °C
Rated current I_n (EF008250)
4 A
Rated voltage (EF000228)
48 V
Degree of protection (IP) (EF005474)
IP65

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-5P-MS/11,5-920/FRC3 SH 1NC with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.